


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





FS2SA 1G FS-Dev Box, Alu 3/4" Crouse-Hinds

Catalog Number	FS2SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FS Device Box, Shallow,
	Copper-Free Aluminum, Single-Gang, 3/4"
Weight per unit	0.5100 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

Features

Cable Entry	(1) End
dimensions	5.1600 IN X 1.8800 IN X 2.7500 IN
Matorial	Natural Finished Sand Conner Free Aluminum

1G FS-DEV BOX, ALU 3/4"

Dimensions and Weight

	~
Ciao	3// in
Size	
OILO	

Descriptions

Description

Description	TO TO DEV DON, THE OF I
extra long description	CRS-H FS2 SA 3/4 THRUFEED CST AL FS
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FS device box, Shallow, Copper-free aluminum, Single-gang, 3/4"
Product Type	3/4 Thrufeed CST AI FS BX SGL GNG MT Lug
Special Features	Configuration Type FS, With Mounting Lug and Ground Screw, Dimension 2-3/4 In Width X 1-7/8 In Depth X 5-5/32 In Height
nufacturar Information	·

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274406107
Manufacturers Part Number	FS2 SA
UPC	782274406107

Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX



Mounting

standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

FLUSH

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Package	5
Weight Per each	0.51
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other

UL 514, CSA C22.2, Federal Specification W-C-5860