

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



G021GZ1B Green P/B Short W Contacts Hubbell--Killark

Catalog Number G021GZ1B Manufacturer Hubbell--Killark Description Killark Go Series Operators Are A Component Use In Conjunction With A Hazardous Location Enclosure to Provide Control Solutions In For; Start/Stop Motor Functions, Led Pilot Light Indications and More. Utilized In Class 1 Division 1 & 2, Class 1 Zone 1 & 2 Areas For Indoor and Outdoor Use. UI Listed and Csa Certified. Weight per unit 0.4900 (lbs/each) Product Category Push Button Complete Assemblie **Features** action Momentary Single Pushbutton actuator amperage rating 10 Contact Configuration 1-NO 0.275A BREAKING @ 250 VDC;0.275A INRUSH @ 250 VDC;0.55A Contact Rating BREAKING @ 125 VDC;0.55A INRUSH @ 125 VDC;1.2A BREAKING @ 600 VAC:1.5A BREAKING @ 480 VAC:10A CARRYING @ 120 VAC;10A CARRYING @ 240 VAC;10A CARRYING @ 480 VAC;10A CARRYING @ 600 VAC;12A INRUSH @ 600 VAC;15A INRUSH @ 480 VAC: 2.5A CARRYING @ 125 VDC: 2.5A CARRYING @ 250 VDC.; 30A INRUSH @ 240 VAC; 3A BREAKING @ 240 VAC; 60A INRUSH @ 120 VAC;6A BREAKING @ 120 VAC Voltage Rating 600 VAC maximum **Dimensions and Weight** Size 6.75 in x 2.25 in x 2 in



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions

Description	GREEN P/B SHORT W CONTACTS
extra long description	KLRK GO21-GZ1B PUSHBUTTON, MOM SHOR
Long Description	Killark GO SERIES Operators are a component use in conjunction with a Hazardous Location enclosure to provide control solutions in for; START/STOP Motor Functions, LED Pilot Light Indications and more. Utilized in Class 1 Division 1 & 2, Class 1 Zone 1 & 2 areas for indoor and outdoor use. UL Listed and CSA Certified.
Product Type	Pushbutton, Mom Short Green 1NO Contacts
Special Features	Killark GO SERIES Operators are a component use in conjunction with a Hazardous Location enclosure to provide control solutions in for;START/STOP Motor Functions, LED Pilot Light Indications and more. Utilized in Class 1 Division 1 & 2, Class 1 Zone 1 & 2 areas for indoor and outdoor use. UL Listed and CSA Certified
Manufacturer Information	
Brand	KILLARK
GTIN	00783936222745
Manufacturers Part Number	GO21-GZ1B
series	GO
UPC	783936222745
Taxonomies, Classifications, and Cat	tegories
	STANDARD DUTY PUSHBUTTONS (10250H-)
Туре	Push Button
Packaging Carton	1
Weight Per each	
Uses, Certifications, and Standards	
Application	G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.
environmental conditions	Hazardous locations
standard	UL, CSA