

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **G1.5X2LG6 LT. Grey Wiring Duct** *Panduit Corporation*

G1.5X2LG6
Panduit Corporation
The G1.5X2LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct Feature A Wide Slot/Finger Design That Provides Greater Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle Sizes. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. 1.5" X 2.0" (38.1 MM X 50.8 MM) and 6' (1.8 M) Long. Cover Sold Separately. Color Light Gray.
2.0 (lbs/each)
Ducts, Raceways, Runways, Tray
Mounting Holes
PVC
Yes
Light Gray
6.00
1.75 x 2.12
1.75
LT. GREY WIRING DUCT
PAN G1.5X2LG6 Panduct® G1.5X2LG6 Ba
The G1.5X2LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct feature a wide slot/finger design that provides greater sidewall rigidity and is suitable with a range of wire bundle sizes. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. 1.5' x 2.0" (38.1 mm x 50.8 mm) and 6' (1.8 m) long. Cover sold separately. Color Light Gray.
Panduct® G1.5X2LG6 Base Wiring Duct
PANDUIT
00074983545797
G1.5X2LG6
074983545797



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

<b>Taxonomies, Classifications, and Cate</b>	gories
Category Description	WIRE DUCT AND COVERS
Туре	Base Wiring Duct
Availability	
minimum qty	6
Packaging	
Carton	6
Package	120
Weight Per each	2
Uses, Certifications, and Standards	
Application	Wide slot/finger design provides greater sidewall rigidity and can be used in a wide range of applications

RoHS Compliant, UL Recognized, CE Compliant; CSA Approved