



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2255 Northwest Parkway SE
30067-0000, GA Marietta
Phone: 678-398-4904
Fax: 678-398-4905



G1X1LG6A SLTD Wiring Duct *Panduit Corporation*

Catalog Number	G1X1LG6A
Manufacturer	Panduit Corporation
Description	The G1X1LG6-A Panduct Lead-Free PVC Wide Slot Wiring Duct Feature A Wide Slot/Finger Design That Provides Greater Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle Sizes. UL 94 Flame Class Of V-0 With A UL Recognized Continuous-Use Temperature Up to 122°F (50°C). Adhesive and Mounting Holes Provided. 1.0" X 1.0" (25.4 MM X 25.4 MM) and 6' (1.8 M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	0.7520 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

Features

connection	Mounting Holes with Adhesive
media	Yes

Material, Color, and Finish

Color	Gray
-------	------

Dimensions and Weight

Length	NA
Size	1.26 x 1.12
Width	1.25

Descriptions

Description	SLTD WIRING DUCT
extra long description	PAN G1X1LG6-A Panduct® G1X1LG6-A B
Long Description	The G1X1LG6-A Panduct Lead-Free PVC Wide Slot Wiring Duct feature a wide slot/finger design that provides greater sidewall rigidity and is suitable with a range of wire bundle sizes. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Adhesive and mounting holes provided. 1.0" x 1.0" (25.4 mm x 25.4 mm) and 6' (1.8 m) long. Cover sold separately. Color Light Gray.
Product Type	Panduct® G1X1LG6-A Base Wiring Duct

Manufacturer Information

Brand	PANDUIT
GTIN	00074983639984
Manufacturers Part Number	G1X1LG6-A
UPC	074983639984



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2255 Northwest Parkway SE
30067-0000, GA Marietta
Phone: 678-398-4904
Fax: 678-398-4905

Taxonomies, Classifications, and Categories

Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Type	Base Wiring Duct

Availability

minimum qty	6
-------------	---

Packaging

Carton	6
Package	120
Weight Per foot	0.752

Uses, Certifications, and Standards

Application	Wide slot/finger design provides greater sidewall rigidity and can be used in a wide range of applications
standard	RoHS Compliant, UL Recognized, CE Compliant, BABA Compliant