

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



G1X1LG6A SLTD Wiring Duct *Panduit Corporation*

*	
Catalog Number	G1X1LG6A
Manufacturer	Panduit Corporation
Description	The G1X1LG6-A Panduct Lead-Free PVC Wide Slot Wiring Duct Feature A Wide Slot/Finger Design That Provides Greater Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle Sizes. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Adhesive and Mounting Holes Provided. 1.0" X 1.0" (25.4 MM X 25.4 MM) and 6' (1.8 M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	
Product Category	Ducts, Raceways, Runways, Tray
Features	
connection	Mounting Holes with Adhesive
Material	PVC
media	Yes
Material, Color, and Finish	
Color	Gray
Dimensions and Weight	
Length	NA
Size	1.26 x 1.12
Width	1.25
Descriptions	
Description	SLTD WIRING DUCT
extra long description	PAN G1X1LG6-A Panduct® G1X1LG6-A B
Long Description	The G1X1LG6-A Panduct Lead-Free PVC Wide Slot Wiring Duct feature a wide slot/finger design that provides greater sidewall rigidity and is suitable with a range of wire bundle sizes. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Adhesive and mounting holes provided. 1.0" x 1.0" (25.4 mm x 25.4 mm) and 6' (1.8 m) long. Cover sold separately. Color Light Gray.
Product Type	Panduct® G1X1LG6-A Base Wiring Duct
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983639984
Manufacturers Part Number	G1X1LG6-A
UPC	074983639984



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Туре	Base Wiring Duct
Availability	
minimum qty	6
Packaging	
Carton	6
Package	120
Weight Per foot	0.752
Uses, Certifications, and Standards	
Application	Wide slot/finger design provides greater sidewall rigidity and can be used in a wide range of applications
standard	CSA Approved;RoHS Compliant, UL Recognized, CE Compliant