

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

G2X2LG6 LT Grey Wiring Ductp/FTPanduit Corporation

Catalog Number	G2X2LG6
Manufacturer	Panduit Corporation
Description	The G2X2IB6 Panduct Lead-Free PVC Wide Slot Wiring Duct Feature A Wide Slot/Finger Design That Provides Greater Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle Sizes. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. 2.0" X 2.0" (50.4 MM X 50.8 MM) and 6' (1.8 M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	
Product Category	Ducts, Raceways, Runways, Tray
Features	
connection	Mounting Holes
Material	PVC
media	Yes
Material, Color, and Finish	
Color	Light Gray
Dimensions and Weight	
Length	NA
Size	2.25 x 2.12
Width	2.25
Descriptions	
Description	LT GREY WIRING DUCTP/FT
extra long description	PAN G2X2LG6 Panduct® G2X2LG6 Base W
Long Description	The G2X2IB6 Panduct Lead-Free PVC Wide Slot Wiring Duct feature a wide slot/finger design that provides greater sidewall rigidity and is suitable with a range of wire bundle sizes. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. 2.0" x 2.0" (50.4 mm x 50.8 mm) and 6' (1.8 m) long. Cover sold separately. Color Light Gray.
Product Type	Panduct® G2X2LG6 Base Wiring Duct
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983545834
Manufacturers Part Number	G2X2LG6
UPC	074983545834



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	WIRE DUCT AND COVERS
Туре	Base Wiring Duct
Availability minimum qty	6
Packaging	
Carton	6
Package	120
Weight Per foot	2
Uses, Certifications, and Standards	
Application	Wide slot/finger design provides greater sidewall rigidity and can be used in a wide range of applications
standard	RoHS Compliant, UL Recognized, CE Compliant; CSA Approved