

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Carton

Weight Per each

GFEP220 Type BR 30 Ma GFI BRKR 20A/2 Pole 120/240V 10K Eaton Corp

Soon	
Catalog Number	GFEP220
Manufacturer	Eaton Corp
Description	Eaton BR Gfci Circuit Breaker, Industrial Ground Fault Thermal-Magnetic Equipment Protector, 20 A, 10 Kaic, Two-Pole 120/240 V, Gfep, Common, #14-4 Awg, Ground Fault Circuit Interrupter, GFI
Weight per unit	0.8000 (lbs/each)
Product Category	20090324154445
Features	
dimensions	5.7500 IN X 3.0000 IN X 4.5000 IN
interrupt rating	10
Poles	2
Voltage Rating	120/240 V
Descriptions	
Description	TYPE BR 30 MA GFI BRKR 20A/2 POLE 120/240V 10K
extra long description	ETN GFEP220 BR 30 mA GFI 20A/2 Pole
Features	Eaton's residential BR Circuit Breakers are used in load centers, panelboards, or similar devices. They are made for a wide range of applications and include: BR 1" circuit breakers and accessories for BR-style load centers; arc fault circuit interrupters (AFCI); and ground fault circuit interrupters (GFCI).
Long Description	Eaton BR GFCI circuit breaker, Industrial ground fault thermal-magnetic equipment protector, 20 A, 10 kAIC, Two-pole, 120/240 V, GFEP, Common, #14-4 AWG, Ground fault circuit interrupter, GFI
Product Type	BR 30 Ma GFI 20A/2 Pole 120/240V 10K
Manufacturer Information	
Brand	Eaton
GTIN	00786676382458
Manufacturers Part Number	GFEP220
UPC	786676382458
Taxonomies, Classifications, and (Categories
Category Description	Fault Sensing Breakers (AFCI/GFCI)
Туре	GFCI circuit breakers
Packaging	
0 1	

1

8.0

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

	a i wai wa
Application	OtherGeneration - Renewable Energy - Alternative
	EnergyDatacenters - IT Space: CI and Hyper ConvergedMarine
	Vessels and Equipment - Marine Vessels and Equipment -
	OtherGeneration - Conventional Energy - Conventional Energy
standard	UL 489