

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GFRST15GY 15A Comm Self Test GFR Gray Hubbell Wiring Devices

04840	
Catalog Number	GFRST15GY
Manufacturer	Hubbell Wiring Devices
Description	Power Protection Devices, Receptacle, Self Test, Gfci, 15A 125V
	2-Pole 3-Wire Grounding, 5-15R, Gray
Weight per unit	0.3500 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
atures	
amperage rating	15
connection	Terminal Screws
Number of Wires	3-Wire Grounding
pallet quantity	
Phase	1
Poles	
Voltage Rating	125
Wattage	1500
Wire Size	#14 to #12
mensions and Weight	
Size	Standard Sized Product
escriptions	
Description	15A COMM SELF TEST GFR GRAY
extra long description	HWDK GFRST15GY 15A COMM SELF TEST G
Features	AUTOGUARD [®] Self Test Technology 1st introduced by Hubbell
	over 10 years agoself test monitoring now required in 2015 U
	943 GFCI Safety Standard Hubbell AUTOGUARD® GFCI
	receptacles continually test and monitor for "people protection
	capability" automatically. This patented safety feature includes
	disconnecting power to the receptacle if critical components ar
	damaged and GFCI protection is lost. GFCI auto-monitoring is
	conducted continuously within every 30 seconds. Also, clear
	visual indicators are pro
Long Description	Power Protection Devices, Receptacle, Self Test, GFCI, 15A 125 2-Pole 3-Wire Grounding, 5-15R, Gray
Product Type	15A Comm Self Test GFR Gray
Special Features	Self-Test



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00883778122026
Manufacturers Part Number	GFRST15GY
series	Heavy Duty
UPC	883778122026
Taxonomies, Classifications, and (Categories
Category Description	Residential Switches
Туре	STANDARD
Availability	
Status	Inactive
Packaging	
Carton	1
Package	10
Weight Per each	0.35
Uses, Certifications, and Standard	S
Application	Commercial Grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-15R
standard	Meets All NEC [®] Requirements