

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GFRST20 20A Comm Self Test GFR Brown Hubbell Wiring Devices

PERO	
Catalog Number	GFRST20
Manufacturer	Hubbell Wiring Devices
Description	Power Protection Devices, Receptacle, Self Test, Gfci, 20A 125V,
-	2-Pole 3-Wire Grounding, 5-20R, Brown
Weight per unit	0.3500 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
eatures	
amperage rating	20
connection	Terminal Scrowe
Number of Wires	
pallet quantity	
Phase	_
Poles	
Voltage Rating	
Wattage	
Wire Size	
) Dimensions and Weight	
Size	Standard Sized Product
escriptions	
Description	20A COMM SELF TEST GFR BROWN
extra long description	HWDK GFRST20 20A COMM SELF TEST GFR
Features	AUTOGUARD [®] Self Test Technology 1st introduced by Hubbell
	over 10 years agoself test monitoring now required in 2015 Ul 943 GFCI Safety Standard Hubbell AUTOGUARD® GFCI
	receptacles continually test and monitor for "people protection
	capability" automatically. This patented safety feature includes
	disconnecting power to the receptacle if critical components are
	damaged and GFCI protection is lost. GFCI auto-monitoring is
	conducted continuously within every 30 seconds. Also, clear visual indicators are pro
Long Description	Power Protection Devices, Receptacle, Self Test, GFCI, 20A 125V
	2-Pole 3-Wire Grounding, 5-20R, Brown
Product Type	20A Comm Self Test GFR Brown
Special Features	Self-Test
	T. 5 (1)



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Bra	nd	WIRING DEVICE-KELLEMS	
GTI	N	00883778122125	
Mai	nufacturers Part Number	GFRST20	
seri	es	Heavy Duty	
UPC	2	883778122125	
Taxonomies, Classifications, and Categories			
Cate	egory Description	Commercial GFCI devices	
Тур	e	STANDARD	
Availability			
Stat	us	Inactive	
Packaging			
Car	-	1	
Pac	kage	10	
We	ight Per each	0.35	
Uses, Certifications, and Standards			
-	lication	Commercial Grade	
env	ironmental conditions	Indoor Dry unless protected by additional means	
Mo	unting	Screw Mount	
nen	na rating	5-20R	
star	ndard	Meets All NEC [®] Requirements	
star	ndard	Meets All NEC [®] Requirements	