

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GK350N 3-1/2" & 4" Form 5 Conduit Body Gasket *Crouse-Hinds*

Catalog Number	GK350N
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 5 Gasket, Neoprene Perforated Center, 3-1/2" or 4"
Weight per unit	0.0900 (lbs/each)
Product Category	Bodies & Covers
Features	
dimensions	5.4700 IN X 0.0600 IN X 14.9300 IN
Form	Form 5
Material, Color, and Finish	
Finish	Untreated

Dimensions and Weight

extra long description

Hub Size 3-1/2 ln, 4 ln

Descriptions

Features	Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h
Long Description	Eaton Crouse-Hinds series Condulet Form 5 gasket, Neoprene, Perforated center, 3-1/2" or 4"
Product Type	3 1/2 and 4 Form 5 Gasket
Special Features	Perforated Center

CRS-H GK350N 3 1/2 AND 4 FORM 5 GAS

Manufacturer Information

Brand	Eaton	
GTIN	00782274756561	
Manufacturers Part Number	GK350N	
UPC	782274756561	

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Gasket



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability Status	Inactive
Packaging	
Carton	1
Package	25
Weight Per each	0.09
Uses, Certifications, and Stand	dards
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 514B, CSA C22.2, CUL