

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GL238 #2 1-Hole Compression Lug 3/8" Bolt *Nsi Industries*

GL238
Nsi Industries
1 Holeshort Barrel Copper Compression Lug W/ PEEPHOLE2 Awg-3/8" Bolt Short Barrel Copper Compression Lugs With Peepholeis A Type Of Copper Compression Connector That Is Produced From High Conductivity Copper Tubing. They Are Tin-Plated to Provide Corrosion Resistance and Are Marked With Die Index and Color Coded For Easy Reference. Listed For 35KV Maximum When Properly Installed.
0.0400 (lbs/each)
Large Terminals & Connectors
2 AWG (STR)
Copper
1
3/8
600 V
1 YEAR
Brown
Tin Plated
L=1.80 - W=.600 - OD=.420 - ID=.310



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_				•	
	\sim	^rı	nti	ions	١
					١
_	S	vı ı	\sim \sim		ì

#2 1-HOLE COMPRESSION LUG 3/8" BOLT
NSI GL238 CU CMP Lug Short 2 AWG 3/
1 HoleShort Barrel Copper Compression Lug w/ PeepHole2 AWG-3/8" Bolt Short Barrel Copper Compression Lugs with PeepHoleis a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
1 HoleShort Barrel Copper Compression Lug w/ PeepHole2 AWG-3/8" Bolt Short Barrel Copper Compression Lugs with PeepHoleis a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Cu CMP Lug Short 2 Awg 3/8 Bolt Size
2 AWG (STR) - 3/8 Mounting Hole

Manufacturer Information

Brand	NSi
GTIN	00662381036056
Manufacturers Part Number	GL238
UPC	662381036056

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Туре	Short Barrel - One Hole

Packaging

Carton	1	
Weight Per each	0.04	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
Mounting	3/8 Mounting Hole
standard	UL486A/B, UL467 (8 AWG -3/0 AWG)