

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GMA125MA 125MA 250V Fa 5X20MM Glass Fuse Bussmann Fuses

Dussinanii ruses	
Catalog Number	GMA125MA
Manufacturer	Bussmann Fuses
Description	Buss Gma-125MA UI Fast Acting 5MM G
Weight per unit	0.0100 (lbs/each)
Product Category	Tools & Testers
Features	
amperage rating	125 mA
connection	Ferrule End X Ferrule End
Response Time	60 Min Maximum at 135%, 2 Min Maximum at 200%
type of indicators	Non-Indicating
Voltage Rating	250 VAC
Dimensions and Weight	
Size	5 mm Diameter X 20 mm Length
Descriptions	
Description	125MA 250V FA 5X20MM GLASS FUSE
Long Description	BUSS GMA-125MA UL Fast Acting 5mm G
Product Type	UI Fast Acting 5MM Glass Fuse 125ma
Special Features	Low Breaking Capacity, Interrupt Rating 35 Amp at 250 Vac, 10
	kA at 125 Vac, Material Glass Tube, Silver Plated Brass End Cap

BrandCooper Bussmann North AmericaGTIN00051712716604Manufacturers Part NumberGMA-125MAUPC051712716604

Taxonomies, Classifications, and Categories

Category Description	GLASS FUSES (and ceramic)
Туре	Electronic, Fast Acting

Availability

-	
Manufacturer Status	Inactive

Packaging

Carton	5
Weight Per each	0.01

Uses, Certifications, and Standards

Application	Electronic Circuits
standard	UL 248-14, CSA, CE