

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### **GMA2A 2A 250V Fa 5X20MM Glass Fuse**

Bussmann Fuses

Catalog Number	GMA2A
Manufacturer	Bussmann Fuses
Description	2A 250V 5MM X 20MM Glass, Fast Acting Fuse
Weight per unit	0.0040 (lbs/each)
Product Category	

#### **Features**

amperage rating	2 AMP
connection	Ferrule End X Ferrule End
Response Time	60 Min Maximum at 135%, 2 Min Maximum at 200%
type of indicators	Non-Indicating
Voltage Rating	250 VAC

#### **Dimensions and Weight**

C!	France Discussion V 20 mans I amount
Size	5 mm Diameter X 20 mm Length

#### **Descriptions**

Description	2A 250V FA 5X20MM GLASS FUSE	
extra long description	EFSE GMA-2A UL Fast Acting 5mm Glas	
Long Description	24 250V Frame v 20mm. Class Fact Acting Fusc	
Product Type	UI Fast Acting 5MM Glass Fuse 2a	
Special Features	Low Breaking Capacity, Interrupt Rating 100 Amp at 250 Vac, 10	
	kA at 125 Vac, Material Glass Tube, Nickel Plated Brass Endcap	

#### **Manufacturer Information**

Brand	Cooper Bussmann North America
GTIN	00051712716673
Manufacturers Part Number	GMA-2A
UPC	051712716673

## **Taxonomies, Classifications, and Categories**

Category Description	GLASS FUSES (and ceramic)
Туре	Electronic, Fast Acting

### **Availability**

•	
Status	Inactive
y ty ty	

# **Packaging**

Carton	5	
Weight Per each	0.004	

# Uses, Certifications, and Standards

Application	Electronic Circuits	
standard	UL 248-14, CSA, CE	