

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



- 1	
- 1	м.
- 1	
- 1	W.
-1	

### **GPD19B 19.5 BLK NM WP Low-Profile Gard'N Post** *Arlington Industries*

Catalog Number	GPD19B
Manufacturer	Arlington Industries
Description	Gard-N-Post. 19.5" Support For Gfci Devices Outdoors. Built In Stabilizers For Extra Stability. Openings In Stabilizers Allow For Insertion Of Extra Support Material. Angle Cut Post For Easy Access to Underground Wiring. Two 1/2" Knockouts. Color Black Color Is Permanent, No Chipping. Clear Extra Duty Weatherproof In Use Cover Installed.
Weight per unit	2.0 (lbs/each)
Product Category	Lighting Accessories
eatures	
Fixture Type	GFCI Device
Material	UV-Rated Plastic
Material, Color, and Finish	
Color	Black with Clear cover
Dimensions and Weight	
Size	L(19.500) x W(6.269) x H(2.964)
Descriptions	
Description	19.5 BLK NM WP LOW-PROFILE GARD'N POST
extra long description	ARL GPD19B POST W/IN USE COVER B
Long Description	Gard-N-Post. 19.5" support for GFCI devices outdoors. Built in stabilizers for extra stability. Openings in stabilizers allow for insertion of extra support material. Angle Cut post for easy access to underground wiring. Two 1/2" Knockouts. Color Black Color is permanent, no chipping. Clear extra duty weatherproof in use cover installed.
Product Type	Post W/In Use Cover B
Special Features	Includes Built In Weatherproof Cover
/lanufacturer Information	
Brand	Arlington Industries
GTIN	00018997770202
Manufacturers Part Number	GPD19B
UPC	018997770202

#### T

Category Description	Poles & Accessories
Type	Low Profile Enclosure



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packagi	ng
---------	----

Carton	1	
Package	6	
Weight Per each	1.98	

#### Uses, Certifications, and Standards

Application	Outdoor, GFCI Device
Mounting	POST
standard	UL and CSA