

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



	GUAT69SA 2" Alu Boo Crouse-Hinds	dy&CVR
Catalog Nu	ımber	GUAT69SA
Manufacturer		Crouse-Hinds
Description		Eaton Crouse-Hinds Series Condulet Gua Conduit Outlet Box With Cover, 5" Cover Opening Diameter, Copper-Free Aluminum, T Shape, 2"
Weight per unit		4.7 (lbs/each)
Product Category		Alum
Features		
Cable Entry		(3) Side
dimensions		7.8800 IN X 4.0300 IN X 6.8100 IN
Dimensions and Weight Size		2 in
Descriptions		
Construction	on	Explosionproof, Dust-Ignitionproof, Raintight
Description	1	2" ALU BODY&CVR
extra long description		CRS-H GUAT69 SA 2 AL OUTL BX 5 DIA
Features		Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th

Manufacturer Information

Long Description

Product Type

Special Features

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274100487
Manufacturers Part Number	GUAT69 SA
UPC	782274100487

2 Al Outl BX 5 Dia CVR THRD Rigid/Imc

shape, 2"

Eaton Crouse-Hinds series Condulet GUA conduit outlet box with cover, 5" cover opening diameter, Copper-free aluminum, T

With Cover, Cover Opening Diameter 5 In

Taxonomies, Classifications, and Categories

Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Туре	Conduit outlet box with cover



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	4.65
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 886, CSA C22.2