



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



GUR1 CRS-H GUR1 1/2-In Expl Proof Box

Crouse-Hinds

Catalog Number	GUR1
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Gur Conduit Outlet Box With Cover, Feraloy Iron Alloy, 1/2"
Weight per unit	3.4 (lbs/each)
Product Category	Bodies & Covers

Features

Cable Entry dimensions	(4) Side, (1) Down 4.1300 IN X 2.6800 IN X 4.1300 IN
------------------------	---

Dimensions and Weight

Size	1/2 in
------	--------

Descriptions

Construction	Explosionproof, Dust-Ignitionproof, Raintight
Description	CRS-H GUR1 1/2-IN EXPL PROOF BOX
extra long description	CRS-H GUR1 1/2 UNV OUTLET BX
Features	Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th
Long Description	Eaton Crouse-Hinds series Condulet GUR conduit outlet box with cover, Feraloy iron alloy, 1/2"
Product Type	1/2 Unv Outlet BX
Special Features	With Cover

Manufacturer Information

Brand	Crouse-Hinds
GTIN	00782274099187
Manufacturers Part Number	GUR1
UPC	782274099187

Taxonomies, Classifications, and Categories

Type	Conduit outlet box with cover
------	-------------------------------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	3.4

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 886, CSA C22.2