

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## H075X025H1T 1/8DIA HTSHRK LBL

Panduit Corporation

Catalog Number	H075X025H1T
Manufacturer	Panduit Corporation
Description	The H075X025H1T Military-Grade Polyolefin Heat-Shrink Label Is
	A Single-Sided Printable. It Offers Crisp, Clear Legends With
	Superior Readability For Quick and Easy Label Production. The
	Heat-Shrink Sleeve Is Designed to Provide A Clear, Reliable, and
	Durable Way to Identify Wires and Cables. Designed For Use With Panduit TDP Printers. Shrink Ratio 3:1. 0.75" X 0.25" (19
	MM X 8.6 MM). Color White. 1000 Labels Per Roll.
Weight per unit	2.3 (lbs/each)
Product Category	
	Markers & Marking rapes
Features	1000
labels per package	
Material	Polyolefin
Printer Type	
Temperature Range	275
Material, Color, and Finish	
Color	White
<b>Dimensions and Weight</b>	
Length	
Size	0.75 x 0.25
Width	0.75
Descriptions	
Description	1/8DIA HTSHRK LBL
extra long description	PAN H075X025H1T H075X025H1T Heatshr
Long Description	The H075X025H1T Military-Grade Polyolefin Heat-Shrink Label is
	a single-sided printable. It offers crisp, clear legends with
	superior readability for quick and easy label production. The
	heat-shrink sleeve is designed to provide a clear, reliable, and
	durable way to identify wires and cables. Designed for use with
	Panduit TDP printers. Shrink ratio 3:1. 0.75" x 0.25" (19 mm x 8.6
Droduct Tuno	mm). Color White. 1000 labels per roll.
Product Type	H075X025H1T Heatshrink, Po, White, Mil Grade, 1000 LBLS, TT,
Manufacturer Information	DANIDUIT
Brand	PANDUIT
GTIN	
Manufacturers Part Number	H075X025H1T
UPC	074983518593



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	HEAT/COLD SHRINK
Туре	Heat Shrink Label
Packaging	
Carton	5
Package	1
Weight Per each	2.3499
Uses, Certifications, and Standards	
standard	Meets UL Standard 224 for flammability and AMS-DTL-23053/5C
	(Class 1 and Class 3). Meets SAE-AS81531, MIL-STD-883F Method
	2015.13, Solutions A, B, and D, and D202F, and MIL-STD-202G
	Method 215K, Solutions A, C, and D when printed with resin or

hybrid ther