

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

H200X084H1T TT, Heat Shrink, 2"X.84", .5 Panduit Corporation

Catalog Number	H200X084H1T	
Manufacturer	Panduit Corporation	
Description	The H200X084H1T Military-Grade Polyolefin Heat-Shrink Label Is A Single-Sided Printable. It Offers Crisp, Clear Legends With Superior Readability For Quick and Easy Label Production. The Heat-Shrink Sleeve Is Designed to Provide A Clear, Reliable, and Durable Way to Identify Wires and Cables. Designed For Use With Panduit TDP Printers. Shrink Ratio 3:1. 2" X 0.84" (50.8 MM X 21.3 MM). Color White. 500 Labels Per Roll.	
Weight per unit		
Product Category	2.3 (lbs/eacn) Markers & Marking Tapes	
Features	g spoo	
labels per package	500	
Material	Polyolefin	
Printer Type	THEDWALL TRANSCER	
Temperature Range	275	
Material, Color, and Finish		
Color	White	
Dimensions and Weight		
Length	NA	
Size	2.00 x 0.84	
Width	2	
Descriptions		
Description	TT,HEAT SHRINK,2"X.84",.5	
extra long description	PAN H200X084H1T H200X084H1T Heatshr	
Long Description	The H200X084H1T Military-Grade Polyolefin Heat-Shrink Label is a single-sided printable. It offers crisp, clear legends with superior readability for quick and easy label production. The heat-shrink sleeve is designed to provide a clear, reliable, and durable way to identify wires and cables. Designed for use with Panduit TDP printers. Shrink ratio 3:1. 2" x 0.84" (50.8 mm x 21.3 mm). Color White. 500 labels per roll.	
Product Type	H200X084H1T Heatshrink, Po, White, Mil Grade, 500 LBLS, TT,	
Manufacturer Information Brand	PANDUIT	
GTIN	00074983526659	
Manufacturers Part Number	H200X084H1T	
LIDC	074002527750	

074983526659



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

de DeliveiLowei	Cost, Quality	/ Products, d	x reisonal c	beivice F	1X: Y30-30U-4

Taxonomies, Classifications, and Cate	gories
Category Description	HEAT/COLD SHRINK
Туре	Heat Shrink Label
Packaging	
Carton	1
Weight Per each	2.3499
Uses, Certifications, and Standards	
standard	Meets UL Standard 224 for flammability and AMS-DTL-23053/5C
	(Class 1 and Class 3). Meets SAE-AS81531, MIL-STD-883F Method
	2015.13, Solutions A, B, and D, and D202F, and MIL-STD-202G
	Method 215K, Solutions A, C, and D when printed with resin or
	hybrid ther