

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



series UPC

## HBL5366CA Plug Angle, 20A 125V, 5-20P, B/W Hubbell Wiring Devices

Catalog Number	HBL5366CA	
Manufacturer	Hubbell Wiring Devices	
Description	Straight Blade Devices, Male Plug, Insulgrip Heavy Duty, Industrial/Commercial Grade, Angled, 2-Pole 3-Wire Grounding 20A 125V, 5-20P, Black and White, Single Pack.	
Weight per unit	0.1500 (lbs/each)	
Product Category	Plugs, Connectors, Inlets, Out	
eatures		
amperage rating	20	
connection		
Cord Type		
Current Rating		
Material	Polycarbonate	
Number of Wires		
pallet quantity		
Phase	1	
Poles	2-Pole	
Voltage Rating	125	
Wattage	2000;2000.0000	
Wire Size	#18 to #10	
imensions and Weight		
Size	1.21 in x 1.52 in x 2.08 in	
escriptions		
Description	PLUG ANGLE, 20A 125V, 5-20P, B/W	
extra long description	HWDK HBL5366CA PLUG ANGLE, 20A 125V	
Long Description	Straight Blade Devices, Male Plug, Insulgrip Heavy Duty,	
	Industrial/Commercial Grade, Angled, 2-Pole 3-Wire Grounding	
	20A 125V, 5-20P, Black and White, Single Pack.	
Product Type	J	
Special Features	Weatherproof Boot	
lanufacturer Information		
Brand	WIRING DEVICE-KELLEMS	
GTIN	00783585174006	
Manufacturers Part Number	HBL5366CA	
series	Insulgrip <sup>®</sup>	

783585174006



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies,	Classifications,	and Categories
	0.0000	

Category Description	Commercial cord connectors
Туре	PLUG
Packaging Carton	1
Dackana	10
Weight Per each	0.15
Uses, Certifications, and Standard	Industrial/Commercial Crade

## Use

Application	Industrial/Commercial Grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Cord
nema rating	5-20P
standard	CSA Certified to C22.2 No. 42 File 280; Fed. Spec.
	W-C596G;NEMA® WD-6 Compliant;UL Listed to UL498 File E1706