


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





HBL8300GY Dup RCPT, HG, 20A 125V, 5-20R, Gy Hubbell Wiring Devices

Catalog Number	HBL8300GY
Manufacturer	Hubbell Wiring Devices
Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-POLE3-Wire Grounding, 20A 125V, 5-20R, Gray, Single Pack.
Weight per unit	0.0860 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro

Features

itui es	
amperage rating	20
connection	Back and Side Wired Screw Terminals
Current Rating	20
Dielectric Strength	Withstands 2,000V minimum
Number of Wires	3-Wire
pallet quantity	4500
Phase	1
Poles	2-Pole
Voltage Rating	125 V
Wattage	2500
Wire Size	#12 to #10

Dimensions and Weight

Descriptions

Description	DUP RCPT, HG, 20A 125V, 5-20R, GY
extra long description	HWDK HBL8300GY DUP RCPT, HG, 20A 12
Features	HBL® Extra Heavy Duty Max Hospital Grade Devices - UL requirements for Hospital Grade devices is more stringent than those for standard devices. Hubbell receptacles are designed to meet and exceed the standards with Exclusive nickel-plated bypass contact design increases contact pressure, lowering the operating temperature; Four point grounding system provides redundant grounding for low resistance ground continuity in high abuse areas; Impact resistant deep face design prevents breakage. Because of these
Long Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole3-Wire Grounding, 20A 125V, 5-20R, Gray, Single Pack.
Product Type	Dup RCPT, HG, 20A 125V, 5-20R, Gy
Special Features	Self Grounding



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

м	١.	_		4	c _	_ 1				c _					
ľ	۱,	12	n	111		CI		·Δr	' In	ГЛ	rr	ทว	1	n	n
	v			u	а	L - I	u	C-1	'In	W		110		w	

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585435749
Manufacturers Part Number	HBL8300GY
series	Hospital Grade
UPC	783585435749

Taxonomies, Classifications, and Categories

Category Description	Industrial receptacles
Туре	RECEPTACLE

Packaging

Carton	1	
Package	10	
Weight Per each	0.086	

Uses, Certifications, and Standards

Application	Extra Heavy Duty Hospital Grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-20R
standard	CSA Certified, C22.2, No. 42 File 285; Fed. Spec. W-C-596; NEMA®
	WD-6 Compliant; UL Listed to UL498 File No. E2186