


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Special Features

HBL8300I Dup RCPT, HG, 20A 125V, 5-20R, Iv Hubbell Wiring Devices

d=15	
Catalog Number	HBL8300I
Manufacturer	Hubbell Wiring Devices
Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Ivory, Single Pack.
Weight per unit	0.0630 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
Features	
amperage rating	20
connection	Pack and Sida Wirod Scrow Torminals
Current Rating	20
Dielectric Strength	
Number of Wires	2.14"
pallet quantity	
Phase	
Poles	2 Polo
Voltage Rating	
Wattage	
Wire Size	#12 to #10
Dimensions and Weight	
Size	3.28 in x 1.65 in x 1.19 in
Descriptions	
Description	DUP RCPT, HG, 20A 125V, 5-20R, IV
extra long description	HWDK HBL8300I DUP RCPT, HG, 20A 125
Features	HBL® Extra Heavy Duty Max Hospital Grade Devices - UL
	requirements for Hospital Grade devices is more stringent than
	those for standard devices. Hubbell receptacles are designed to
	meet and exceed the standards with Exclusive nickel-plated
	bypass contact design increases contact pressure, lowering the
	operating temperature; Four point grounding system provides
	redundant grounding for low resistance ground continuity in hig
	abuse areas; Impact resistant deep face design prevents
	breakage. Because of these
Long Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Ivory, Single Pack.
Product Type	Dup RCPT, HG, 20A 125V, 5-20R, Iv
A 1.E.	

Self Grounding



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Inform	

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585435725
Manufacturers Part Number	HBL8300I
series	Hospital Grade
UPC	783585435725

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories	
Type	RECEPTACLE	

Packaging

Carton	1	
Package	10	
Weight Per each	0.063	

Uses, Certifications, and Standards

Application	Extra Heavy Duty Hospital Grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-20R
standard	CSA Certified, C22.2, No. 42 File 285; Fed. Spec. W-C-596; NEMA®
	WD-6 Compliant; UL Listed to UL498 File No. E2186