

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBL9965C LKG Plug, 3P3W, 20A 125/250V, B/W Hubbell Wiring Devices

Catalog Number	HBL9965C	
Manufacturer	Hubbell Wiring Devices	
Description	Locking Devices, Twist-Lock®, Industrial, Male Insulgrip® Plug,	
	20A 125/250V, 3-Pole 3-Wire Non Grounding, Non-Nema, Screw	
	Terminal, Black and White Nylon.	
Weight per unit	0.1580 (lbs/each)	
Product Category	Plugs, Connectors, Inlets, Out	
itures		
amperage rating	20	
connection	Screwed Terminal	
Cord Type	All Listed Portables	
Current Rating	20	
Material	Nylon	
Number of Wires	3-Wire	
pallet quantity	2880	
Phase	1	
Poles	2 Dolo	
Voltage Rating	125/250	
Wattage	5	
Wire Size	#16 to #8	
nensions and Weight		
Size	2.26 in x 2.26 in x 2.75 in	
scriptions		
Description	LKG PLUG, 3P3W, 20A 125/250V, B/W	
extra long description	HWDK HBL9965C LKG PLUG, 3P3W, 20A 1	
Long Description	Locking Devices, Twist-Lock®, Industrial, Male Insulgrip® Plug,	
	20A 125/250V, 3-Pole 3-Wire Non Grounding, Non-NEMA, Screv	
	Terminal, Black and White nylon.	
Product Type	LKG Plug, 3P3W, 20A 125/250V, B/W	
Special Features	Standard Product	
nufacturer Information		
Brand	WIRING DEVICE-KELLEMS	
GTIN	00783585037608	
Manufacturers Part Number	HBL9965C	
UPC	783585037608	



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies	, Classifications,	and Categories
-------------------	--------------------	----------------

Category Description	NEMA RATED TURNLOK PLUGS, CONNEC	JIORS, & RECEPTICLES
Туре	Plugs	
Packaging		
Carton	1	
Package	30	
Weight Per each	0.158	

Uses, Certifications, and Standards

Application .	Extra Heavy Duty Industrial
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Cord
nema rating	Non-NEMA
standard	Certified to CSA C22.2 No.42; Fed. Spec. W-C-596; Listed to UL 498