

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBLDS60 NM Sloped Disc, 60A Unfused, 4X *Hubbell Wiring Devices*

Catalog Number	HBLDS60
Manufacturer	Hubbell Wiring Devices
Description	Industrial Grade, Motor Disconnect Switch, Unfused, 3 Pole, 60A 600V Ac, Screw Terminals, IP69K, Nema Type 4X, 12 Non-Metallic Sloped Top Enclosure, Culus, NSF, Ce, UI 508 / UI 60947-4-1a
Weight per unit	6.1 (lbs/each)
Product Category	20240715143619
Features	
operating cycles	10,000
Descriptions	
Description	NM SLOPED DISC, 60A UNFUSED, 4X
extra long description	HWDK HBLDS60 NM SLOPED DISC, 60A UN
Features	NEC section 430.102(B) requires each motor controller to have a disconnect within line of sight from the motor and driven equipment. Hubbell's Circuit-Lock® Unfused Disconnect Switches are UL listed as a manual motor controller and also "suitable as a motor disconnect" and meet these code requirements.
Long Description	Industrial Grade, Motor Disconnect Switch, Unfused, 3 Pole, 60A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure, cULus, NSF, CE, UL 508 / UL 60947-4-1A
Product Type	NM Sloped Disc, 60A Unfused, 4X
Manufacturer Information	·
Brand	WIRING DEVICE-KELLEMS
GTIN	00783585763224
Manufacturers Part Number	HBLDS60
series	Non-Fused
UPC	783585763224
Taxonomies, Classifications, and (Categories
Category Description	France O France Assessment
Туре	Disconnect Switches
Packaging Carton	1
Package	0
Weight Per each	6.05
-	

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Heavy Duty Industrial and/or Washdown
Enclosure	IP69k and UL Type 4X, 12
environmental conditions	Indoor and Outdoor
standard	cULus Listed