



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## HSTT1948Q Heatshrnk Tubing 3/16 BLK

*Panduit Corporation*

Catalog Number	HSTT1948Q
Manufacturer	Panduit Corporation
Description	The HSTT19-48-Q Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.187" Diameter X 4' Long (4.8 MM X 1.2 M). Color Black. 25 Per Package.
Weight per unit	0.8350 (lbs/each)
Product Category	Insulating Materials

### Features

flammability	Flame Retardant
media	Yes
outside diameter	0.187
Shrink Ratio	2:1

### Material, Color, and Finish

Color	Black
-------	-------

### Dimensions and Weight

Thickness	0.02
-----------	------

### Descriptions

Description	HEATSHRNK TUBING 3/16 BLK
extra long description	PAN HSTT19-48-Q Dry-Shrink™ HSTT19-
Long Description	The HSTT19-48-Q Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.187" Diameter x 4' Long (4.8 mm x 1.2 m). Color Black. 25 per package.
Product Type	Dry-Shrink™ HSTT19-48-Q Heatshrink, Black, Po, 4' L, 0.187"

### Manufacturer Information

Brand	PANDUIT
GTIN	00074983905904
Manufacturers Part Number	HSTT19-48-Q
UPC	074983905904



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
----------------------	------------------

## Packaging

Carton	25
--------	----

Weight Per each	0.835
-----------------	-------

## Uses, Certifications, and Standards

Application	For Dry Locations;Insulating and protecting wires and cables
-------------	--

standard	Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770
----------	---