ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

HSTT25C 1/4"X100' BLK Thin Wall HS

Panduit Corporation

Catalog Number	HSTT25C
Manufacturer	Panduit Corporation
Description	The HSTT25-C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.25” Diameter X 100’ Long (6.4 MM X 30.5 M). Color Black. 1 Roll.
Weight per unit	1.1 (lbs/each)
Product Category	Insulating Materials

Features

flammability	Flame Retardant
media	Yes
outside diameter	0.25
Shrink Ratio	2:1

Material, Color, and Finish

Color	Black

Dimensions and Weight

Thickness	0.025

Descriptions

Description	1/4"X100' BLK THIN WALL HS
extra long description	PAN HSTT25-C Dry-Shrink™ HSTT25-C H
Long Description	The HSTT25-C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.25” Diameter x 100’ Long (6.4 mm x 30.5 m). Color Black. 1 roll.
Product Type	Dry-Shrink™ HSTT25-C Heatshrink, Black, Po, 100' L, 0.25" to

Manufacturer Information

Brand	Panduit®
GTIN	00074983747030
Manufacturers Part Number	HSTT25-C
UPC	074983747030

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Type	Heat-Shrink

Packaging

Carton	1
Weight Per roll	1.14

Uses, Certifications, and Standards

Application	For Dry Locations;Insulating and protecting wires and cables
standard	Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770