

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

IBE22LMMV0LT40K 165W Led Hbay 21067LM 4K *Lithonia Lighting - Acuity*

Catalog Number	IBE22LMMV0LT40K
Manufacturer	Lithonia Lighting - Acuity
Description	The I-Beam [®] Ibe Led Luminaire Gives Budget-Conscious
	Customers A Reliable Led Solution Featuring 6KV Surge
	Protection Standard and Is Designed to Meet The Challenges Of
	Warehouse and Light Industrial Applications.
Weight per unit	10.2 (lbs/each)
Product Category	Led Highbay Lighting
Features	
average life	100
connection	Hardwired
dimensions	22 x 16.25 x 5.25
Fixture Type	HIGH BAY
Hardware	Yes
Lamp Included	Yes
Lamp Type	LED - Static
lumens	22,000
Material	Aluminum
Power Source	Hardwired
Shape	Rectangular
Voltage Rating	120-277
Warranty	
Wattage	166
Material, Color, and Finish	
Color	White
Finish	Gloss
Lens Color	WHITE
Lens Material	Acrylic
Dimensions and Weight	
Height	4.27
Length	21.93
Size	22x16.25x5.25 IN
Width	14.83



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions
Construction

Descriptions	
Construction	New Construction, Remodel
Description	165W LED HBAY 21067LM 4K
extra long description	LITH IBE 22LM MVOLT 40K LED economi
Features	Contractor Select
Long Description	The I-BEAM [®] IBE LED luminaire gives budget-conscious customers a reliable LED solution featuring 6kV surge protection standard and is designed to meet the challenges of warehouse and light industrial applications.
Product Type	High Bay
Manufacturer Information	
Brand	Lithonia Lighting
GTIN	00191848491195
Manufacturers Part Number	IBE 22LM MVOLT 40K
UPC	191848491195
Taxonomies, Classifications, and (Categories
Category Description	
Туре	HIGH BAY
Packaging	
Carton	1
Weight Per each	10.15
Uses, Certifications, and Standard	ls
Application	Manufacturing, Warehouses
environmental conditions	Indoor
Mounting	Pendant,Surface,Suspended
standard	cUL,UL