




# NSI Industries Inc.

# B

## DUAL RATED CONNECTORS FOR ALUMINUM AND COPPER CABLES

### INSULATION PIERCING CONNECTORS IPC SERIES



Self-insulated, insulation piercing, bolted connectors. They perform as a splice or tap, for non-tension applications. The insulation piercing capability eliminates both conductor insulation stripping and the necessity for taping the connection after installation.

- Eliminates need for conductor insulation stripping.
- UL 486B listed AL9CU (90°C rated).
- For use on insulated conductor only.
- No taping required after installation.
- For copper-to-copper, copper-to-aluminum and aluminum-to-aluminum applications

| CAT. NO. | NAED NO. | CONDUCTOR RANGE AL9CU |         | NO. OF BOLTS | SHPG. WT. LBS/100 | CARTON QTY. | NET PRICE EACH |           |
|----------|----------|-----------------------|---------|--------------|-------------------|-------------|----------------|-----------|
|          |          | MAIN                  | TAP     |              |                   |             | 1-4            | 5 OR MORE |
|          |          |                       |         |              |                   |             | CARTONS        | CARTONS   |
| IPC1002* | 08250    | 1/0-8                 | 2-8     | 1            | 25                | 6           | 10.50          | 8.65      |
| IPC4010  | 08251    | 4/0-1/0               | 1/0-6   | 2            | 56                | 4           | 19.40          | 16.20     |
| IPC4040  | 08252    | 4/0-1/0               | 4/0-1/0 | 2            | 56                | 4           | 20.90          | 17.35     |
| IPC3540  | 08253    | 350-4/0               | 4/0-10  | 1            | 76                | 6           | 43.20          | 35.90     |
| IPC3535  | 08254    | 350-4/0               | 350-4/0 | 2            | 127               | 6           | 53.80          | 44.70     |
| IPC5040* | 08255    | 500-350               | 4/0-4   | 1            | 106               | 4           | 57.95          | 48.10     |

\*600 volts, balance 300 volts.

TEL. (704)596-1978    FAX (704)596-2770  
 CALL TOLL FREE    1-800-321-5847  
 OR    1-800-321-LUGS




# NSI Industries Inc.

# B

## DUAL RATED CONNECTORS FOR ALUMINUM AND COPPER CABLES

### INSULATION PIERCING CONNECTORS IPC SERIES



Self-insulated, insulation piercing, bolted connectors. They perform as a splice or tap, for non-tension applications. The insulation piercing capability eliminates both conductor insulation stripping and the necessity for taping the connection after installation.

- Eliminates need for conductor insulation stripping.
- UL 486B listed AL9CU (90°C rated).
- For use on insulated conductor only.
- No taping required after installation.
- For copper-to-copper, copper-to-aluminum and aluminum-to-aluminum applications

| CAT. NO. | NAED NO. | CONDUCTOR RANGE AL9CU |         | NO. OF BOLTS | SHPG. WT. LBS/100 | CARTON QTY. | NET PRICE EACH |           |
|----------|----------|-----------------------|---------|--------------|-------------------|-------------|----------------|-----------|
|          |          | MAIN                  | TAP     |              |                   |             | 1-4            | 5 OR MORE |
|          |          |                       |         |              |                   |             | CARTONS        | CARTONS   |
| IPC1002* | 08250    | 1/0-8                 | 2-8     | 1            | 25                | 6           | 10.50          | 8.65      |
| IPC4010  | 08251    | 4/0-1/0               | 1/0-6   | 2            | 56                | 4           | 19.40          | 16.20     |
| IPC4040  | 08252    | 4/0-1/0               | 4/0-1/0 | 2            | 56                | 4           | 20.90          | 17.35     |
| IPC3540  | 08253    | 350-4/0               | 4/0-10  | 1            | 76                | 6           | 43.20          | 35.90     |
| IPC3535  | 08254    | 350-4/0               | 350-4/0 | 2            | 127               | 6           | 53.80          | 44.70     |
| IPC5040* | 08255    | 500-350               | 4/0-4   | 1            | 106               | 4           | 57.95          | 48.10     |

\*600 volts, balance 300 volts.

TEL. (704)596-1978    FAX (704)596-2770  
 CALL TOLL FREE    1-800-321-5847  
 OR    1-800-321-LUGS