




NSI Industries Inc.

B

DUAL RATED CONNECTORS FOR ALUMINUM AND COPPER CABLES

INSULATION PIERCING CONNECTORS IPC SERIES



Self-insulated, insulation piercing, bolted connectors. They perform as a splice or tap, for non-tension applications. The insulation piercing capability eliminates both conductor insulation stripping and the necessity for taping the connection after installation.

- Eliminates need for conductor insulation stripping.
- UL 486B listed AL9CU (90°C rated).
- For use on insulated conductor only.
- No taping required after installation.
- For copper-to-copper, copper-to-aluminum and aluminum-to-aluminum applications

CAT. NO.	NAED NO.	CONDUCTOR RANGE AL9CU		NO. OF BOLTS	SHPG. WT. LBS/100	CARTON QTY.	NET PRICE EACH	
		MAIN	TAP				1-4 CARTONS	5 OR MORE CARTONS
		IPC1002*	08250				1/0-8	2-8
IPC4010	08251	4/0-1/0	1/0-6	2	56	4	19.40	16.20
IPC4040	08252	4/0-1/0	4/0-1/0	2	56	4	20.90	17.35
IPC3540	08253	350-4/0	4/0-10	1	76	6	43.20	35.90
IPC3535	08254	350-4/0	350-4/0	2	127	6	53.80	44.70
IPC5040*	08255	500-350	4/0-4	1	106	4	57.95	48.10

*600 volts, balance 300 volts.

TEL. (704)596-1978 FAX (704)596-2770
 CALL TOLL FREE 1-800-321-5847
 OR 1-800-321-LUGS




NSI Industries Inc.

B

DUAL RATED CONNECTORS FOR ALUMINUM AND COPPER CABLES

INSULATION PIERCING CONNECTORS IPC SERIES



Self-insulated, insulation piercing, bolted connectors. They perform as a splice or tap, for non-tension applications. The insulation piercing capability eliminates both conductor insulation stripping and the necessity for taping the connection after installation.

- Eliminates need for conductor insulation stripping.
- UL 486B listed AL9CU (90°C rated).
- For use on insulated conductor only.
- No taping required after installation.
- For copper-to-copper, copper-to-aluminum and aluminum-to-aluminum applications

CAT. NO.	NAED NO.	CONDUCTOR RANGE AL9CU		NO. OF BOLTS	SHPG. WT. LBS/100	CARTON QTY.	NET PRICE EACH	
		MAIN	TAP				1-4	5 OR MORE
							CARTONS	CARTONS
IPC1002*	08250	1/0-8	2-8	1	25	6	10.50	8.65
IPC4010	08251	4/0-1/0	1/0-6	2	56	4	19.40	16.20
IPC4040	08252	4/0-1/0	4/0-1/0	2	56	4	20.90	17.35
IPC3540	08253	350-4/0	4/0-10	1	76	6	43.20	35.90
IPC3535	08254	350-4/0	350-4/0	2	127	6	53.80	44.70
IPC5040*	08255	500-350	4/0-4	1	106	4	57.95	48.10

*600 volts, balance 300 volts.

TEL. (704)596-1978 FAX (704)596-2770
 CALL TOLL FREE 1-800-321-5847
 OR 1-800-321-LUGS