

ELLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



IPLD2503C 6AWG-250 MCM 3 Port Connector

IPLDZOUSC OAVVG-ZO	
Nsi Industries	

Catalog Number	IPLD2503C
Manufacturer	Nsi Industries
Description	The Polaris IPLD250-3C Multi-Tap Dual-Sided Entry Vision Tap Connector Features 3 Ports Sized For 250 MCM - 6 Awg Wires. The Clear Body Allows Users to See Their Conductor Placement and Is Wrapped In A Layer Of Plastisol Insulation. Each Dual-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Installs With A Hex Key and Torque Wrench, Without Any Tape or Additional Supplies. Designed For Use In A Wide Range Of Splicing Applicat
Weight per unit	
Product Category	Large Terminals & Connectors
Features	
Material	Aluminum
Number of Conductors	3
Poles	1
Voltage Rating	600
Warranty	1 YEAR
Wire Size	
Wire Type	Class B & C
Material, Color, and Finish	
Color	Clear
Finish	Plastisol Insulated
Dimensions and Weight Size	L=2.930 - W=2.280 - H=2.180



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions		
Description	6AWG-250 MCM 3 PORT CONNECTOR	
extra long description	NSI IPLD250-3C POLARIS Multi Tap 25	
Features	The Polaris IPLD250-3C 3-Port Dual-Sided Connector provides the simplest solution for forming a secure connection between up to three conductors in applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 250 MCM - 6 AWG	
	wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated connector options using just a hex key and torque wrench. The clear body lets installers see their work for optima	
Long Description	The Polaris IPLD250-3C Multi-Tap Dual-Sided Entry Vision Tap Connector features 3 ports sized for 250 MCM - 6 AWG wires. The clear body allows users to see their conductor placement and is wrapped in a layer of plastisol insulation. Each dual-sided port is pre-loaded with an oxide inhibitor, with removable access plugs over the hex screws used to tighten the connections. Installs with a hex key and torque wrench, without any tape or additional supplies. Designed for use in a wide range of splicing applicat	
Product Type	Polaris Multi Tap 250 5 Port Dse Bagged	
Special Features	(3) 250 MCM-6 AWG - Dual Rated	
Manufacturer Information		
Brand	Polaris	
GTIN	00662381996497	
Manufacturers Part Number	IPLD250-3C	
UPC	662381996497	
Taxonomies, Classifications, and Categories		
Category Description	Comp & Mech Lugs and Butt Splices	
Туре	Double Sided Entry	
Packaging		
Carton	6	
Weight Per each	0.35	
Uses, Certifications, and Standards		
Application	Wire Termination	
Enclosure	Clear Plastisol	
environmental conditions	Dry Location Only	
standard	UL 486A/B	
Temperature Rating	90	