

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Size

IPLD3506 350MCM-#6 6 Pole Polaris Connector Block Nsi Industries

Catalog Number	IPLD3506		
Manufacturer	Nsi Industries		
Description	The Polaris IPLD350-6 Multi-Tap Dual-Sided Entry Black Connector Features 6 Ports Sized For 350 MCM - 6 Awg Wires. The Body Is Made From Aluminum Alloy Wrapped In A Layer Of Plastisol Insulation. Each Dual-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Installs With A Hex Key and Torque Wrench, Without Any Tape or Additional Supplies. Designed For Use In A Wide Range Of Splicing Applications, Including Installation In Cable		
Weight per unit	1.1 (lbs/each)		
Product Category	Large Terminals & Connectors		
Features			
Material	Aluminum		
Number of Conductors	6		
Poles	1		
Voltage Rating	600 V		
Warranty	1 YEAR		
Wire Size	350 MCM-6 AWG		
Wire Type	Class B & C		
Material, Color, and Finish			
Color	Black		
Finish	Plastisol Insulated		
Dimensions and Weight			
Ciao	L / /70 N/ 2410 H 2/10		

L=6.670 - W=2.410 - H=2.610



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	•		
11000	rın	tian	
Desc	,	11()	•
200			•

standard

Temperature Rating

des the en up to I boards, wires n x key d in		
en up to I boards, wires n x key d in		
vires		
high-dielectric stren The Polaris IPLD350-6 Multi-Tap Dual-Sided Entry Black Connector features 6 ports sized for 350 MCM - 6 AWG wires. The body is made from aluminum alloy wrapped in a layer of plastisol insulation. Each dual-sided port is pre-loaded with an oxide inhibitor, with removable access plugs over the hex screws used to tighten the connections. Installs with a hex key and torque wrench, without any tape or additional supplies. Designed for use in a wide range of splicing applications, including installation in cable		
Polaris		
00662381924049		
IPLD350-6		
i		

UL 486A/B

90 C