

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

JDL4 4A 600V Class J Time Delay Fuse Edison Fuses

| Catalog Number | JDL4 |
|---------------------------|---|
| Manufacturer | Edison Fuses |
| Description | Eaton Edison Series JDL Fuse, Time-Delay Current-Limiting Fuse, Non-Indicating, 4 A, Class J, Non-Indicating, 200 Kaic, Standard, 10, 600 V |
| Weight per unit | 0.0010 (lbs/each) |
| Product Category | Dual Element |
| Features | |
| amperage rating | 4 A |
| class | Class J |
| dimensions | 2.2500 IN X 0.8100 IN X 0.8100 IN |
| interrupt rating | 200 kAIC |
| media | Yes |
| Voltage Rating | 600 V |
| Descriptions | |
| Description | 4A 600V CLASS J TIME DELAY FUSE |
| extra long description | EFSE JDL4 UL CLASS J TIME DELAY |
| Features | Edison's UL Class J fuse products are offered in both Dual-Element Time-Delay (JDL) and Fast-Acting (JFL) types. Both types have 200,000 amp interrupting rating at 600Vac RMS Sym amps. Their small physical size and high performance characteristics makes Class J fuses ideal for any space-limited applications. Edison's JFL fuses are best suited for the protection of non-inductive loads such as resistive heating and lighting circuits. |
| Long Description | Eaton Edison series JDL fuse, Time-delay current-limiting fuse, Non-indicating, 4 A, Class J, Non-indicating, 200 kAIC, Standard, 10, 600 V |
| Product Type | UI Class J Time Delay |
| Special Features | Non-Indicating |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00782634249153 |
| Manufacturers Part Number | JDL4 |

782634249153



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Taxonomies, Classifications, and Categories | |
|---|--|
| Category Description | Fuses & Fuse Accessories |
| Туре | FUSE |
| Packaging | |
| Carton | 1 |
| Package | 10 |
| Weight Per each | 0.001 |
| Uses, Certifications, and Standards | |
| Application | Datacenters - Facilities: Critical Power |

CSA Certified, UL Listed, RoHS Compliant, CE Marked