



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## K100CM 1" FM5 CST CVR

*Crouse-Hinds*

Catalog Number	K100CM
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 5 Cover, Cast Iron, 1"
Weight per unit	0.3300 (lbs/each)
Product Category	Bodies & Covers

### Features

dimensions	5.3100 IN X 1.7500 IN X 0.1900 IN
Form	Form 5

### Material, Color, and Finish

Finish	Electrogalvanized With Aluminum Acrylic Painted
--------	---

### Dimensions and Weight

Hub Size	1 in
----------	------

### Descriptions

Description	1" FM5 CST CVR
extra long description	MIDWEST K100CM 1 FORM 5 CAST COVER
Features	Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h
Long Description	Eaton Crouse-Hinds series Condulet Form 5 cover, Cast iron, 1"
Product Type	1 Form 5 Cast Cover

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564002693
Manufacturers Part Number	K100CM
UPC	784564002693

### Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	COVER



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Package	25
Weight Per each	0.33

## Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 514B, CSA C22.2, CUL