









U5000 STANDARD MODELS






| CATALOG # | RECEPTACLES | | CIRCUIT BREAKERS | |
|----------------|--|---|--|---|
| ◆ U5000-XL-41 | (1) TT30R (1) 5-20R GFI |  | (1) 30A, 1P, 120V (1) 20A, 1P, 120V |  |
| ◆ U5000-XL-332 | (2) TT30R (1) 5-20R GFI |  | (2) 30A, 1P, 120V (1) 20A, 1P, 120V |  |
| ◆ U5000-XL-55 | (1) 14-50R (1) 5-20R GFI |  | (1) 50A, 2P, 120/240V (1) 20A, 1P, 120V |  |
| ◆ U5000-XL-75 | (1) 14-50R (1) TT30R (1) 5-20R GFI |  | (1) 50A, 2P, 120/240V (1) 30A, 1P, 120V (1) 20A, 1P, 120V |  |
| U5000-XL-75GB | (1) 14-50R (1) TT30R (1) 5-20R | | (1) 50A, 2P, 120/240V (1) 30A, 1P, 120V (1) 20A, 1P, 120V, GFI | |

U5000 STANDARD BASE MODEL

Order up to (3) receptacle / breaker kits. Sold separately for field installation.

| CATALOG # | DESCRIPTION |
|------------|---|
| ◆ U5000-XL | Base model without receptacles or circuit breakers. |

RECEPTACLE & CIRCUIT BREAKER KITS

| CATALOG # | RECEPTACLES | CIRCUIT BREAKERS | CONDUCTORS | CONFIGURATION |
|---------------|------------------|--------------------|------------|--|
| ◆ K5400-520GR | 5-20R Duplex GFI | 20 Amp, 1 Pole | 12 Awg |  GFI Rec. |
| ◆ K5400-520GB | 5-20R Duplex | 20 Amp, 1 Pole GFI | 12 Awg |  GFI CB |
| ◆ K5400-TT30 | TT30R | 30 Amp, 1 Pole | 10 Awg |  |
| K5400-TT30GB | TT30R | 30 Amp, 1 Pole GFI | 10 Awg |  GFI CB |
| ◆ K5400-1450 | 14-50R | 50 Amp, 2 Pole | 8 Awg |  |









◆ Stock model. Availability subject to prior sale.

Note: 20 Amp GFI required at each RV site by UL and NEC 551-71

INTERNAL LIGHT KITS Factory or field installed. See accessory page.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements before ordering or installing equipment in this catalog.

U5000 STANDARD MODELS






| CATALOG # | RECEPTACLES | | CIRCUIT BREAKERS | |
|----------------|--|---|--|---|
| ◆ U5000-XL-41 | (1) TT30R (1) 5-20R GFI |  | (1) 30A, 1P, 120V (1) 20A, 1P, 120V |  |
| ◆ U5000-XL-332 | (2) TT30R (1) 5-20R GFI |  | (2) 30A, 1P, 120V (1) 20A, 1P, 120V |  |
| ◆ U5000-XL-55 | (1) 14-50R (1) 5-20R GFI |  | (1) 50A, 2P, 120/240V (1) 20A, 1P, 120V |  |
| ◆ U5000-XL-75 | (1) 14-50R (1) TT30R (1) 5-20R GFI |  | (1) 50A, 2P, 120/240V (1) 30A, 1P, 120V (1) 20A, 1P, 120V |  |
| U5000-XL-75GB | (1) 14-50R (1) TT30R (1) 5-20R | | (1) 50A, 2P, 120/240V (1) 30A, 1P, 120V (1) 20A, 1P, 120V, GFI | |

U5000 STANDARD BASE MODEL

Order up to (3) receptacle / breaker kits. Sold separately for field installation.

| CATALOG # | DESCRIPTION |
|------------|---|
| ◆ U5000-XL | Base model without receptacles or circuit breakers. |

RECEPTACLE & CIRCUIT BREAKER KITS

| CATALOG # | RECEPTACLES | CIRCUIT BREAKERS | CONDUCTORS | CONFIGURATION |
|---------------|------------------|--------------------|------------|--|
| ◆ K5400-520GR | 5-20R Duplex GFI | 20 Amp, 1 Pole | 12 Awg |  GFI Rec. |
| ◆ K5400-520GB | 5-20R Duplex | 20 Amp, 1 Pole GFI | 12 Awg |  GFI CB |
| ◆ K5400-TT30 | TT30R | 30 Amp, 1 Pole | 10 Awg |  |
| K5400-TT30GB | TT30R | 30 Amp, 1 Pole GFI | 10 Awg |  GFI CB |
| ◆ K5400-1450 | 14-50R | 50 Amp, 2 Pole | 8 Awg |  |

◆ Stock model. Availability subject to prior sale.

Note: 20 Amp GFI required at each RV site by UL and NEC 551-71

INTERNAL LIGHT KITS Factory or field installed. See accessory page.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements before ordering or installing equipment in this catalog.