



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



KLU3000 3000A 600V TD Class L Fuse

Bussmann Fuses

Catalog Number	KLU3000
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Klu Fuse, Fast-Acting Fuse, 3000 A, Class L, Non-Indicating, Bolted Blade End X Bolted Blade End, 5 Sec At 500%, 200 Kaic At 600 Vac, Bolt, Standard, 1, 600 V
Weight per unit	16.9 (lbs/each)
Product Category	Current Limiting

Features

amperage rating	3000 A
class	Class L
connection	Bolted Blade End X Bolted Blade End
dimensions	10.7500 IN X 5.0000 IN X 5.0000 IN
interrupt rating	200 kAIC at 600 Vac
media	Yes
Response Time	5 sec at 500%
Voltage Rating	600 V

Dimensions and Weight

Size	5.00 In Diameter X 10.75 In Length
------	------------------------------------

Descriptions

Description	3000A 600V TD CLASS L FUSE
extra long description	BUSS KLU-3000 LIMITRON TIME DELAY F
Features	Bussmann's broad line of UL Class L fuses includes the KRP-C-SP Low-Peak family of fuses offering unsurpassed dual-element, current-limiting, time-delay performance and interrupting ratings of 300kA RMS Sym. Complementing the Low-Peak family are our Limitron products offering both Fast-acting and economical time-delay performance in our KTU, KLU, and KRP-CL products
Long Description	Eaton Bussmann series KLU fuse, Fast-acting fuse, 3000 A, Class L, Non-indicating, Bolted blade end x bolted blade end, 5 sec at 500%, 200 kAIC at 600 Vac, Bolt, Standard, 1, 600 V
Product Type	Limitron Time Delay Fuse
Special Features	Non-Indicating

Manufacturer Information

Brand	Eaton
GTIN	00051712497039
Manufacturers Part Number	KLU-3000
UPC	051712497039



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description Fuses & Fuse Accessories

Type FUZE

Packaging

Carton 1

Weight Per each 16.85

Uses, Certifications, and Standards

Application Ind Facilities & Factories - Facility: Safety and Security Systems

Mounting Bolt

standard CE Marked, RoHS Compliant