

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





KSU29 #1-250 Split Bolt Conn Burndy LLC

Description Tin- Sep Len and Weight per unit Product Category Larg Features Material Cop Descriptions Description extra long description Long Description Tin- sep tha	Plated, High Strength Copper Alloy Servit With Spacer. Spacer erates Dissimilar Conductors and Provides Long Contact gth That Prevents High Pressure Point Contacts Between Run Tap Conductors, 2.50 In L. 570 (lbs/each) ge Terminals & Connectors
Sep Len and Weight per unit Product Category Larg Features Material Cop Descriptions Description #1- extra long description Long Description Tin- sep tha	erates Dissimilar Conductors and Provides Long Contact gth That Prevents High Pressure Point Contacts Between Run Tap Conductors, 2.50 In L. 570 (lbs/each) ge Terminals & Connectors per
Weight per unit 0.56 Product Category Larg Features Material Cop Descriptions Description #1-: extra long description BUF Long Description Tin- sep tha	per 250 SPLIT BOLT CONN
Product Category Large Features Material Copescriptions Description #1-: extra long description BUF Long Description Tinesep that	per 250 SPLIT BOLT CONN
Material Cop Descriptions Description #1-: extra long description BUF Long Description Tin- sep tha con	250 SPLIT BOLT CONN
Descriptions Description #1- extra long description BUF Long Description Tin- sep tha	250 SPLIT BOLT CONN
Description #1-: extra long description BUF Long Description Tin- sep tha con	
Description #1-: extra long description BUF Long Description Tin- sep tha con	
Long Description Tin- sep tha con	
sep tha con	R KSU29 SERVIT UNIV 1-250
Decil at Torre	plated, high strength copper alloy SERVIT with spacer. Spacer erates dissimilar conductors and provides long contact length prevents high pressure point contacts between run and tap ductors, 2.50 IN L.
Product Type Serv	vit Univ 1-250
Special Features Fea Spa Lon Bet Con Inst AAA And	tures: Tin-Plated, High Strength Copper Alloy SERVIT With cer, Spacer Separates Dissimilar Conductors And Provides g Contact Length That Prevents High Pressure Point Contacts ween Run And Tap Conductors, Use Of PENETROX Joint appound Recommended With Aluminum And ACSR, allation Torque: 650 IN-LB, Conductor Type: Run: ACSR, 5005, AC, Commercial Stranded Aluminum, Commercial Stranded Solid Copper, Tap: ACSR, 5005, AAAC, Commercial Stranded Minum, Commercial Stranded And Solid Copper
Manufacturer Information	
Brand BUF	RNDY
GTIN 007	81810036853
Manufacturers Part Number KSU	29
UPC 781	810036853

Taxo

Category Description	SPLIT BOLTS
Type	KSU, Universal



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

ack		

Uses, Certifications, and Standards

Application	For All Combinations Of Copper, Aluminum, ACSR, AAAC, 5005,
	And Steel