

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



KSU29 #1-250 Split Bolt Conn Burndy LLC

| Catalog Number | KSU29 |
|-----------------------------------|--|
| Manufacturer | Burndy LLC |
| Description | Tin-Plated, High Strength Copper Alloy Servit With Spacer. Space Seperates Dissimilar Conductors and Provides Long Contact Length That Prevents High Pressure Point Contacts Between Rur and Tap Conductors, 2.50 In L. |
| Weight per unit | 0.5670 (lbs/each) |
| Product Category | Large Terminals & Connectors |
| eatures | |
| Material | Copper |
| Descriptions | |
| Description | #1-250 SPLIT BOLT CONN |
| extra long description | BUR KSU29 SERVIT UNIV 1-250 |
| Long Description | Tin-plated, high strength copper alloy SERVIT with spacer. Space seperates dissimilar conductors and provides long contact lengtl that prevents high pressure point contacts between run and tap conductors, 2.50 IN L. |
| Product Type | Servit Univ 1-250 |
| Special Features | Features: Tin-Plated, High Strength Copper Alloy SERVIT With Spacer, Spacer Separates Dissimilar Conductors And Provides Long Contact Length That Prevents High Pressure Point Contacts Between Run And Tap Conductors, Use Of PENETROX Joint Compound Recommended With Aluminum And ACSR, Installation Torque: 650 IN-LB, Conductor Type: Run: ACSR, 5005 AAAC, Commercial Stranded Aluminum, Commercial Stranded And Solid Copper, Tap: ACSR, 5005, AAAC, Commercial Stranded Aluminum, Commercial Stranded And Solid Copper |
| Manufacturer Information | |
| Brand | BURNDY |
| GTIN | 00781810036853 |
| Manufacturers Part Number | KSU29 |
| UPC | 781810036853 |
| axonomies, Classifications, and C | Categories |
| Category Description | SPLIT BOLTS |
| outegoly Description | KSU, Universal |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

| Carton | 1 |
|-----------------|-------|
| Package | |
| Weight Per each | 0.567 |

Uses, Certifications, and Standards

Application

For All Combinations Of Copper, Aluminum, ACSR, AAAC, 5005, And Steel