

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



L614 #6 1-Hole Long Barrel Compression Lug 1/4" Bolt

Nsi Industries	ong Barrer Compression Lug 174 Bort				
Catalog Number	L614				
Manufacturer	Nsi Industries				
Description	Compression Lug, #8 Awg Conductor Size, #6 Awg Conductor Size, Non-Insulated, Copper Conductor Material, Blue Insulation Color, 1 Conductor, +90 °C Operating Temperature, 1.772 In Overall Length, 600 V, 0.02 LB/Ea				
Weight per unit	-				
Product Category	Large Terminals & Connectors				
eatures					
Cable Size	# 6 AWG (STR)				
Material	Copper				
Number of Holes					
Stud Size					
Voltage Rating	600 V				
Warranty	1 YEAR				
laterial, Color, and Finish Color	Blue				
imensions and Weight Size	L=1.77 - W=.420 - OD=.300 - ID=.200				
	L-1.77 - W420 - OD300 - ID200				
escriptions	#/ 1 HOLE LONG DADDEL COMPDESSION LLIC 1/4" DOLT				
Description	#6 1-HOLE LONG BARREL COMPRESSION LUG 1/4" BOLT				
extra long description Features	NSI L614 CU CMP Lug Long 6 AWG 1/4				
reatures	1 Hole Long Barrel Copper Compression Lug 6 AWG - 1/4" Bolt Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. They are tin-plated to provide corrosion low contact resistance. Marked with die index and color coded for easy reference. Listed for 35KV maximum wher properly installed and to cable manufacturer instructions. Temperature rating 90 degrees C.				
lanufacturer Information					
GTIN	00662381034007				
UPC	662381034007				
axonomies, Classifications, and	l Categories				
Category Description	Comp & Mech Lugs and Butt Splices				
Туре	Long Barrel - One Hole				



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

a				

Carton	1	
Package	100	
Weight Per each	0.02	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
Mounting	1/4 Mounting Hole
standard	UL486A/B, UL467 (8 AWG -3/0 AWG)