

### ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**UPC** 

## LAM2A350125 Al Lug 1H 2B 6AWG 1/2" Stud Panduit Corporation

Catalog Number	LAM2A350125	
Manufacturer	Panduit Corporation	
Description	The LAM2A350-12-5 Tin-Plated Aluminum Mechanical Lug, One-Hole, Two Barrel, Is Made From Extruded Aluminum Alloy to Provide Premium Electrical and Mechanical Performance For Wide Wire Range-Taking Capability That Helps Minimize Inventory Requirements. The Plated Steel or Aluminum Set Screw Provides A Durable Electrical Contract Between Conductor and	
	Lug. UI Listed and Csa Certified For Use Up to 600 V and UI Temperature Rated 90 Degrees Celsius.	
Weight per unit	·	
Product Category	Tools & Testers	
eatures		
amperage rating	NA	
insulation	Non-Insulated	
media	Yes	
Number of Holes		
Stud Size	1/2	
Voltage Rating	600	
escriptions		
Description	AL LUG 1H 2B 6AWG 1/2" STUD	
extra long description		
Long Description	The LAM2A350-12-5 Tin-Plated Aluminum Mechanical Lug, one-hole, two barrel, is made from extruded aluminum alloy to provide premium electrical and mechanical performance for wide wire range-taking capability that helps minimize inventory requirements. The plated steel or aluminum set screw provides a durable electrical contract between conductor and Lug. UL Listed and CSA Certified for use up to 600 V and UL temperature rated 90 Degrees Celsius.	
Product Type	Pan-Lug™ LAM2A350-12-5 Al Mech, 350KCMIL, Tin PLT, 1HOLE, 1/2"ST	
lanufacturer Information		
Brand	PANDUIT	
GTIN	00613056878440	
Manufacturers Part Number	LAM2A350-12-5	

613056878440



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Category Description	SPLIT BOLTS
Туре	Mechanical Lug

#### **Packaging**

onaging	
Carton	1
Weight Per each	0.276

### Uses, Certifications, and Standards

**Taxonomies, Classifications, and Categories** 

Application	Stranded Aluminum or Copper Code Conductor
Mounting	1.13
standard	cULus Listed for use up to 600V & Temperature Rated to 90°C