



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



LAMA214C Al Mech, 2, Tin PLT, 1HOLE, 1/4" Stud *Panduit Corporation*

Catalog Number	LAMA214C
Manufacturer	Panduit Corporation
Description	The LAMA2-14-C Tin-Plated Aluminum Mechanical Lug, One-Hole, Single Barrel, Is Made From Extruded Aluminum Alloy to Provide Premium Electrical and Mechanical Performance For Wide Wire Range-Taking Capability That Helps Minimize Inventory Requirements. The Plated Steel or Aluminum Set Screw Provides A Durable Electrical Contract Between Conductor and Lug. UL Listed and Csa Certified For Use Up to 600 V and UL Temperature Rated 90 Degrees Celsius.
Weight per unit	0.5690 (lbs/each)
Product Category	Tools & Testers

Features

amperage rating	NA
insulation	Non-Insulated
media	Yes
Number of Holes	1
Stud Size	1/4
Voltage Rating	600

Descriptions

Description	AL MECH,2, TIN PLT, 1HOLE, 1/4" STUD
extra long description	PAN LAMA2-14-C Pan-Lug™ LAMA2-14-C
Long Description	The LAMA2-14-C Tin-Plated Aluminum Mechanical Lug, one-hole, single barrel, is made from extruded aluminum alloy to provide premium electrical and mechanical performance for wide wire range-taking capability that helps minimize inventory requirements. The plated steel or aluminum set screw provides a durable electrical contract between conductor and Lug. UL Listed and CSA Certified for use up to 600 V and UL temperature rated 90 Degrees Celsius.
Product Type	Pan-Lug™ LAMA2-14-C Al Mech, 2, Tin PLT, 1HOLE, 1/4" Stud, PK1

Manufacturer Information

Brand	PANDUIT
GTIN	00613056878488
Manufacturers Part Number	LAMA2-14-C
UPC	613056878488



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description.....SPLIT BOLTS

Type.....Mechanical Lug

Packaging

Carton.....1

Weight Per each.....0.569

Uses, Certifications, and Standards

Application.....Stranded Aluminum or Copper Code Conductor

Mounting.....0.47

standard.....cULus Listed for use up to 600V & Temperature Rated to 90°C