

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GTIN

UPC

Manufacturers Part Number

LB58 1-1/2" LB FM8 Cond Body

Catalog Number	LB58
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 8 Conduit Outlet Body, Feraloy Iron Alloy, LB Shape, 1-1/2"
Weight per unit	4.3 (lbs/each)
Product Category	Bodies & Covers
Features	
dimensions	9.1300 IN X 2.7500 IN X 4.0300 IN
Form	Form 0
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	4-1/32
Hub Size	
Length	
Width	2 2/4
Descriptions	
	1-1/2" LB FM8 COND BODY
Description extra long description	
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 8 bodies are offered in seven different shapes to provide the most flexible offering on the market. Form 8 Condulet outlet bodies provide more room for heavier conductors. Many shapes and sizes are available for rigic threaded conduit. Two cover screws on all body sizes provide tight
Long Description	Eaton Crouse-Hinds series Condulet Form 8 conduit outlet body, Feraloy iron alloy, LB shape, 1-1/2"
Product Type	1 1/2 LB Form 8 THRD Rigid Outlet Body
Manufacturer Information	
Brand	Eaton

00782274515205

782274515205

LB58



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging	
Carton	2
Weight Per each	4.25
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other

UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D