

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



# LB59 1-1/2" Alu LB MK9 Cond Body Crouse-Hinds

Catalog Number	LB59
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Mark 9 Conduit Outlet Body,
	Copper-Free Aluminum, LB Shape, 1-1/2"
Weight per unit	1.5 (lbs/each)
Product Category	Alum
aturos	

#### **Features**

dimensions 7.7800 IN X 2.5000 IN X 3.8800 IN

### Material, Color, and Finish

=		
E1 - 1 - 1 -	11.1.	
Finish	LINTE	93189
1 11 1131 1	Onti	atcu

### **Dimensions and Weight**

Height	3-3/4
Hub Size	1-1/2 in
Length	7-3/4
Width	2-1/2

### **Descriptions**

Description	1-1/2" ALU LB MK9 COND BODY
extra long description	CRS-H LB59 1 1/2 LB MARK 9 THRD RIG
Features	Mark 9 copper-free aluminum conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide for access to conductors for maintenance and future system changes. Mark 9 bodies are offered in seven different shapes, and they provide more room for heavier conductors.
Long Description	Eaton Crouse-Hinds series Condulet Mark 9 conduit outlet body, Copper-free aluminum, LB shape, 1-1/2"
Product Type	1 1/2 LB Mark 9 THRD Rigid Outlet Body

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274515304
Manufacturers Part Number	LB59
UPC	782274515304

# **Taxonomies, Classifications, and Categories**

Category Description	Form 9 condulets, covers & gaskets
Туре	Conduit outlet body



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

a				

Carton	2
Weight Per each	1.5

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D