

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LBD3300 1" LBD Cond Body *Crouse-Hinds*

Catalog Number	LBD3300
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet LBD Mogul Conduit Body, Feraloy Iron Alloy, 1"
Weight per unit	2.4 (lbs/each)
Product Category	Bodies & Covers

Features

connection	Threaded
dimensions	6.2500 IN X 1.8100 IN X 2.9400 IN

Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted	
--	--

Dimensions and Weight

Height	2-15/16	
Hub Size	1 in	
Length	6-1/4	
Width	1-13/16	

Descriptions

Description	1" LBD COND BODY
extra long description	CRS-H LBD3300 1 IRON MOGUL OUTLET B
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet LBD mogul conduit body, Feraloy iron alloy, 1"
Product Type	1 Iron Mogul Outlet Body 90 Deg
Special Features	With Cover and Neoprene Gasket
nufacturar Information	

Manufacturer Information

Brand	Eaton
GTIN	00782274518305
Manufacturers Part Number	LBD3300
UPC	782274518305



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications,	and Categories
Category Description	FORM

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Magul conduit hady
Packaging	
Carton	1
Package	5
	2.44

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D