



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



LBR6AL02SWW1ARLS 6" 13/19/25W Led Downlight 3K/35K/4K/5K 120-277V *Lithonia Lighting - Acuity*

Catalog Number	LBR6AL02SWW1ARLS
Manufacturer	Lithonia Lighting - Acuity
Description	LBR Is Everything You Need In A Downlight At An Affordable Price. Whether It'S The Seamless Install From-Below Design, Abundant Energy Savings or Maintaining Glare-Free Aesthetics, LBR Is The Perfect Solution For Any Renovation, Remodel or New Construction Project.
Weight per unit	2.5 (lbs/each)
Product Category	Lighting

Features

average life	60,000
dimnable	Yes
Lamp Included	Yes
Lamp Type	LED - Static
lumens	1000 LM,1500 LM,2000 LM,Switchable
Maximum Operating Temperature	25
Power Source	Plug-In
Shape	Round
Voltage Rating	120-277
Warranty	5
Wattage	25.6

Material, Color, and Finish

Color	Clear
color rendering index (cri)	80
color temperature	Variable
Finish	Semi-Specular

Descriptions

Construction	New Construction,Retrofit
Description	6" 13/19/25W LED DOWNLIGHT 3K/35K/4K/5K 120-277V
extra long description	LITH LBR6 ALO2 SWW1 AR LSS MWD MVOL
Features	Contractor Select
Long Description	LBR is everything you need in a downlight at an affordable price. Whether it's the seamless install from-below design, abundant energy savings or maintaining glare-free aesthetics, LBR is the perfect solution for any renovation, remodel or new construction project.
Product Type	Retrofit Kit



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Lithonia Lighting
GTIN	00194994825081
Manufacturers Part Number	LBR6 ALO2 SWW1 AR LSS MWD MVOL
UPC	194994825081

Taxonomies, Classifications, and Categories

Category Description	LED GENERAL PURPOSE LIGHTING
Type	RETROFIT KIT

Trade Size

aperture size	6 in
---------------	------

Packaging

Carton	1
Weight	6.421
Weight Per each	2.51

Uses, Certifications, and Standards

Application	Education,Hospitality,House of Worship,Offices & Banks,Retail,Retrofit
environmental conditions	Indoor
Mounting	Recessed
standard	ULENERGY STAR,Low UGR