ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

LCA414L 4AWG 1HOLE Lug
Panduit Corporation

Catalog Number	LCA414L
Manufacturer	Panduit Corporation
Description	The LCA4-14-L Tin-Plated Copper Compression Lug, One-Hole, Standard Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. Ul Listed and Csa Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	0.0260 (lbs/each)
Product Category	Large Terminals & Connectors

Features

Material	Copper
media	Yes
Number of Holes	1
Stud Size	1/4

Material, Color, and Finish

Color	Gray

Dimensions and Weight

Size	#4 — #3 AWG Code STR, #2 AWG Code SOL

Descriptions

Description	4AWG 1HOLE LUG
extra long description	PAN LCA4-14-L Pan-Lug™ LCA4-14-L Co
Long Description	The LCA4-14-L Tin-Plated Copper Compression Lug, one-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperature rated to 90°C.
Product Type	Pan-Lug™ LCA4-14-L Comp. Lug, 4, Tin PLT Copper, STRT, One 1
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V

Manufacturer Information

Brand	PANDUIT
GTIN	0007498390 0114
Manufacturers Part Number	LCA4-14-L
UPC	074983900114

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Compression Lug

Packaging

Carton	50
Weight Per each	0.026

Uses, Certifications, and Standards

Mounting	7/8
standard	UL listed to 486A-486B File #E52164 and CSA certified C22.2 No. 65-13