

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LCCX238DE #2 2HOLE 3/8SP FL

Panduit Corporation

Manufacturer Panduit Corporation Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, Two-He Long Barrel, Has Color-Coded Barrels Marked With Panduit an Specified Competitor Die Index Numbers For Proper Crimp Die Selection. The Long Barrel Maximizes The Number Of Crimps a Provides Premium Wire Pull-Out Strength and Performance. The Generously Beveled Wire Entry Prevents Bent Back Strands Winserting The Conductor Into The Barrel. UI Listed and Csa Certified. Weight per unit 1.6 (lbs/each) Product Category Large Terminals & Connectors Features Material Tin-Plated Copper Material Yes Number of Holes 2 Stud Size 3/8 Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Description Description #2 2HOLE 3/8SP FL extra long description #2 2HOLE 3/8SP FL extra long description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-holong barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps an provides premium wire pull-out strength and performance. Ty generously beveled wire entry prevents bent back strands whinserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	Catalog Number	LCCX238DE
Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, Two-Hc Long Barrel, Has Color-Coded Barrels Marked With Panduit an Specified Competitor Die Index Numbers For Proper Crimp Die Selection. The Long Barrel Maximizes The Number Of Crimps of Provides Premium Wire Pull-Out Strength and Performance. T Generously Beveled Wire Entry Prevents Bent Back Strands W Inserting The Conductor Into The Barrel. UI Listed and Csa Certified. Weight per unit 1.6 (Ibs/each) Product Category Large Terminals & Connectors Features Material Tin-Plated Copper media Yes Number of Holes 2 Stud Size 3/8 Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description PAN LCCX2-38D-E 7 Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps an provides premium wire pull-out strength and performance. Th generously beveled wire entry prevents bent back strands wh inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	_	
Features Material Tin-Plated Copper media Yes Number of Holes 2 Stud Size 3/8 Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps an provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands whinserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction		The LCCX2-38D-E Tin-Plated Copper Compression Lug, Two-Hole, Long Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. The Long Barrel Maximizes The Number Of Crimps and Provides Premium Wire Pull-Out Strength and Performance. The Generously Beveled Wire Entry Prevents Bent Back Strands When Inserting The Conductor Into The Barrel. UI Listed and Csa
Features Material Tin-Plated Copper media Yes Number of Holes 2 Stud Size 3/8 Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-holong barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands whe inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	Weight per unit	1.6 (lbs/each)
Material media Yes Number of Holes Stud Size 3/8 Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description extra long description Long Description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description Fine LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands whe inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	Product Category	
Material Tin-Plated Copper media Yes Number of Holes 2 Stud Size 3/8 Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands whinserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	Features	
Number of Holes 2 Stud Size 3/8 Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions #2 2HOLE 3/8SP FL extra long description extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D-Long Description Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-holong barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands who inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features	Material	Tin-Plated Copper
Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps an provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands whinserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	media	Yes
Material, Color, and Finish Color Brown Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps an provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands whe inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	Number of Holes	2
Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands when inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	Stud Size	3/8
Dimensions and Weight Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands whe inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	0.1	D.
Size #2 AWG Class B, C, G, H, I, K, M and DLO Descriptions Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands who inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	Color	Brown
Description #2 2HOLE 3/8SP FL extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands who inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Consult cable manufacturer for voltage stress relief instruction	0'	#2 AWG Class B, C, G, H, I, K, M and DLO
extra long description PAN LCCX2-38D-E Pan-Lug™ LCCX2-38D- Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands when inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Consult cable manufacturer for voltage stress relief instruction	Descriptions	
Long Description The LCCX2-38D-E Tin-Plated Copper Compression Lug, two-ho long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands who inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction	Description	#2 2HOLE 3/8SP FL
long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands who inserting the conductor into the barrel. UL Listed and CSA Certified. Product Type Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two Special Features Consult cable manufacturer for voltage stress relief instruction		
Special Features Consult cable manufacturer for voltage stress relief instruction	Long Description	long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands when inserting the conductor into the barrel. UL Listed and CSA
·	3.	Pan-Lug™ LCCX2-38D-E Comp. Lug, Tin PLT Copper, STRT, Two 3/
with applications greater than 2000 v	Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

M	anufac	turer In	forma	tion
---	--------	----------	-------	------

Brand	PANDUIT	
GTIN	00074983425570	
Manufacturers Part Number	LCCX2-38D-E	
UPC	074983425570	

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Туре	Compression Lug

Packaging

onagnig		
Carton	1	
Package	20	
•		

Uses, Certifications, and Standards

Mounting	1-7/16
standard	CSA certified C22.2 No. 65-13, UL Listed to 486A-486B File
	#E52164, ABS approved