


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





LD3600 3 Pole LD 600A BRKR Eaton Corp

Soon	
Catalog Number	LD3600
Manufacturer	Eaton Corp
Description	Eaton Series C Complete Molded Case Circuit Breaker, L-Frame, LD, Complete Breaker, Fixed Thermal, Fixed Magnetic Trip, Three-Pole, 600 A, 600 Vac, 250 VDC, 65 Kaic At 240 Vac, 35 Kaic At 480 Vac, Aluminum, Line and Load, 50/60 HZ
Weight per unit	20.4 (lbs/each)
Product Category	3 Pole Interchangeable Trip TH
Features	
Current Rating	600 A
dimensions	8.2500 IN X 8.2500 IN X 8.0000 IN
media	Yes
Poles	3

Fixed thermal, fixed magnetic

Descriptions

Trip Type Voltage Rating

Description	3 POLE LD 600A BRKR
extra long description	ETN LD3600 600A, 600VAC, 3 pole the
Features	Experience the superior quality of the Eaton Series C Molded Case Circuit Breaker. The Series C circuit breaker is ideal for panelboards, switchboards, motor control centers, and busway applications. Choose from a premier selection of trip units including thermal magnetic, electronic, and magnetic only switches. Available for systems up to 600 VAC or 250 VDC with current ratings up to 800A.
Long Description	Eaton Series C complete molded case circuit breaker, L-frame, LD, Complete breaker, Fixed thermal, Fixed magnetic trip, Three-pole, 600 A, 600 Vac, 250 Vdc, 65 kAIC at 240 Vac, 35 kAIC at 480 Vac, Aluminum, Line and load, 50/60 Hz
Product Type	600A, 600VAC, 3 Pole Thermal Magnetic Ci

600 VAC, 250 VDC

Manufacturer Information

Brand	Eaton	
GTIN	00786679341827	
Manufacturers Part Number	LD3600	
UPC	786679341827	

Taxonomies, Classifications, and Categories

	•	•	J
Ţ	уре		Molded case circuit breaker



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	20.4
Uses, Certifications, and Standards	
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
Frequency Rating	50 to 60 Hz
standard	UL 489