



# LED Dimmable Recessed Retrofits

TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

### Limitless options for the following applications:

- Dimmable 6", 5" & 4" downlight applications

### Great features and benefits:

- 120W, 85W, 75W, 65W and 50W BR40/BR30/R20 downlight replacement options
- Excellent color consistency (CRI)
- Smooth, uniform dimming from 100% - 0.5%
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- Available in 2700K, 3000K, 4100K and 5000K
- Easy installation — pigtail and spring clips



4" Dimmable HiCRI Recessed Retrofit



5/6" Dimmable HiCRI Recessed Retrofit

90 CRI  
50 R9



4" Dimmable Recessed Retrofit



5/6" Dimmable Recessed Retrofit



LED  
we know light.™





# LED Dimmable Recessed Retrofits Specifications

|            |  |
|------------|--|
| <b>LED</b> | 35,000 hours average rated life, 120 volts |
|------------|--|

## Applications:

Ideal for dimmable 6", 5" & 4" downlight applications



Perfect for retrofit or new construction recessed downlight applications

## Features and Benefits

- 5/6" unit ideal for replacing dimmable 65W, 85W and 120W incandescent alternatives in 5" and 6" recessed cans
- 4" unit ideal for replacing 50W and 75W incandescent alternatives in a 4" recessed can
- Excellent Color Consistency and CRI
- Smooth, uniform dimming
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- UL approved for damp locations
- Easy installation and integrated trim
- Shatter Resistant



LDRACCGU24 – GU24 Adapter

|                |      |
|----------------|------|
| Catalog Number |      |
| Notes          | Type |



## Specifications

|                          | 14W        | 11W        | 10W        | 9W         |
|--------------------------|------------|------------|------------|------------|
| Recessed Downlight Size: | 5", 6"     | 5", 6"     | 4"         | 4"         |
| Input Line Voltage:      | 120 VAC    | 120 VAC    | 120 VAC    | 120 VAC    |
| Input Power              | 14 W       | 11 W       | 10 W       | 9 W        |
| Input Line Frequency     | 50/60HZ    | 50/60HZ    | 50/60HZ    | 50/60HZ    |
| Lamp Life (Rated)        | 35,000 hrs | 35,000 hrs | 35,000 hrs | 35,000 hrs |
| Minimum Starting Temp    | -30°C      | -30°C      | -30°C      | -30°C      |

IC-rated for direct contact with insulation



- LED11DR5627K
- LED11DR5630K
- LED11DR5641K
- LED11DR5650K
- LED14DR5627K
- LED14DR5630K
- LED14DR5641K
- LED14DR5650K



- LED10DR427K
- LED10DR430K
- LED10DR435K
- LED10DR441K
- LED10DR450K



- L11DR56D3527K95
- L11DR56D3530K95



- L9DR4D3527K95
- L9DR4D3530K95



**5 YEAR WARRANTY\***

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP AUG 2017/WF72602.ALL





# LED Dimmable Recessed Retrofits Specifications

Smooth Uniform Dimming

## 5/6" Recessed Retrofits

| Item #   | ENERGY STAR rated | Description                             | Life Hours | Replacement | Voltage | Wattage | Lumens | LPW  | CCT   | CRI | Case Qty |
|--|-------------------|---|------------|-------------|---------|---------|--------|------|-------|-----|----------|
| <b>Downlight Retrofits compatible with 5/6" recessed cans</b>        |                   |   |            |             |         |         |        |      |       |     |          |
| LED14DR5627K   | ★                 | LED 14W 5/6" Recessed Downlight - 2700K | 35,000     | 120         | 120     | 14      | 1250   | 89.3 | 2700K | 80  | 6        |
| LED14DR5630K   | ★                 | LED 14W 5/6" Recessed Downlight - 3000K | 35,000     | 120         | 120     | 14      | 1300   | 92.9 | 3000K | 80  | 6        |
| LED14DR5641K   | ★                 | LED 14W 5/6" Recessed Downlight - 4100K | 35,000     | 120         | 120     | 14      | 1300   | 92.9 | 4100K | 80  | 6        |
| LED14DR5650K   | ★                 | LED 14W 5/6" Recessed Downlight - 5000K | 35,000     | 120         | 120     | 14      | 1350   | 96.4 | 5000K | 80  | 6        |
| LED11DR5627K   | ★                 | LED 11W 5/6" Recessed Downlight - 2700K | 35,000     | 85          | 120     | 11      | 800    | 72.7 | 2700K | 80  | 6        |
| LED11DR5630K   | ★                 | LED 11W 5/6" Recessed Downlight - 3000K | 35,000     | 85          | 120     | 11      | 850    | 77.3 | 3000K | 80  | 6        |
| LED11DR5641K   | ★                 | LED 11W 5/6" Recessed Downlight - 4100K | 35,000     | 85          | 120     | 11      | 900    | 81.8 | 4100K | 80  | 6        |
| LED11DR5650K   | ★                 | LED 11W 5/6" Recessed Downlight - 5000K | 35,000     | 85          | 120     | 11      | 950    | 86.4 | 5000K | 80  | 6        |
| <b>Hi CRI Downlight Retrofits compatible with 5/6" recessed cans</b> |                   |   |            |             |         |         |        |      |       |     |          |
| L11DR56D3527K95**  | ★                 | LED 11W 5/6" Recessed Downlight - 2700K | 35,000     | 65          | 120     | 11      | 700    | 63.6 | 2700K | 90  | 6        |
| L11DR56D3530K95**  | ★                 | LED 11W 5/6" Recessed Downlight - 3000K | 35,000     | 65          | 120     | 11      | 750    | 68.2 | 3000K | 90  | 6        |

## 4" Recessed Retrofits

|  |   |                                       |        |    |     |    |     |      |       |    |   |
|--|---|---------------------------------------|--------|----|-----|----|-----|------|-------|----|---|
| <b>Downlight Retrofits compatible with 4" recessed cans</b>        |   |                                       |        |    |     |    |     |      |       |    |   |
| LED10DR427K  | ★ | LED 10W 4" Recessed Downlight - 2700K | 35,000 | 75 | 120 | 10 | 750 | 75.0 | 2700K | 80 | 6 |
| LED10DR430K  | ★ | LED 10W 4" Recessed Downlight - 3000K | 35,000 | 75 | 120 | 10 | 750 | 75.0 | 3000K | 80 | 6 |
| LED10DR435K  |   | LED 10W 4" Recessed Downlight - 3500K | 35,000 | 75 | 120 | 10 | 620 | 62.0 | 3500K | 80 | 6 |
| LED10DR441K  | ★ | LED 10W 4" Recessed Downlight - 4100K | 35,000 | 75 | 120 | 10 | 800 | 80.0 | 4100K | 80 | 6 |
| LED10DR450K  | ★ | LED 10W 4" Recessed Downlight - 5000K | 35,000 | 75 | 120 | 10 | 800 | 80.0 | 5000K | 80 | 6 |
| <b>Hi CRI Downlight Retrofits compatible with 4" recessed cans</b> |   |                                       |        |    |     |    |     |      |       |    |   |
| L9DR4D3527K95**  | ★ | LED 9W 4" Recessed Downlight - 2700K  | 35,000 | 50 | 120 | 9  | 550 | 61.1 | 2700K | 90 | 6 |
| L9DR4D3530K95**  | ★ | LED 9W 4" Recessed Downlight - 3000K  | 35,000 | 50 | 120 | 9  | 550 | 61.1 | 3000K | 90 | 6 |

### Accessory

LDRACCGU24      GU24 Adapter

\*JAB Compliant

+All Plastic Body



**5 YEAR WARRANTY\***

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP AUG 2017/WF72602.ALL



# CREATING BEAUTY

TCP has a **20-year history in energy-efficient lighting.**

Thanks to our **cutting edge technology** and manufacturing

expertise, we have shipped billions of high quality lamps and our

**integrated technology** and manufacturing

provides **expedited time-to-market.** With TCP, you can

count on unique lighting products designed to meet very specific needs—

lighting that transforms your surroundings and envelopes you in warmth—

**lighting that generates beauty** with every flip of the switch.

# LED

For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | F: 877-487-0516





# LED Dimmable Recessed Retrofits

TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

## Limitless options for the following applications:

- Dimmable 6", 5" & 4" downlight applications

## Great features and benefits:

- 120W, 85W, 75W, 65W and 50W BR40/BR30/R20 downlight replacement options
- Excellent color consistency (CRI)
- Smooth, uniform dimming from 100% - 0.5%
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- Available in 2700K, 3000K, 4100K and 5000K
- Easy installation — pigtail and spring clips



4" Dimmable HiCRI Recessed Retrofit



5/6" Dimmable HiCRI Recessed Retrofit

90 CRI  
50 R9



4" Dimmable Recessed Retrofit



5/6" Dimmable Recessed Retrofit



LED  
we know light.™





# LED Dimmable Recessed Retrofits Specifications

|            |  |
|------------|--|
| <b>LED</b> | 35,000 hours average rated life, 120 volts |
|------------|--|

## Applications:

Ideal for dimmable 6", 5" & 4" downlight applications



Perfect for retrofit or new construction recessed downlight applications

## Features and Benefits

- 5/6" unit ideal for replacing dimmable 65W, 85W and 120W incandescent alternatives in 5" and 6" recessed cans
- 4" unit ideal for replacing 50W and 75W incandescent alternatives in a 4" recessed can
- Excellent Color Consistency and CRI
- Smooth, uniform dimming
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- UL approved for damp locations
- Easy installation and integrated trim
- Shatter Resistant



LDRACCGU24 – GU24 Adapter

|                |      |
|----------------|------|
| Catalog Number |      |
| Notes          | Type |



## Specifications

|                          | 14W        | 11W        | 10W        | 9W         |
|--------------------------|------------|------------|------------|------------|
| Recessed Downlight Size: | 5", 6"     | 5", 6"     | 4"         | 4"         |
| Input Line Voltage:      | 120 VAC    | 120 VAC    | 120 VAC    | 120 VAC    |
| Input Power              | 14 W       | 11 W       | 10 W       | 9 W        |
| Input Line Frequency     | 50/60HZ    | 50/60HZ    | 50/60HZ    | 50/60HZ    |
| Lamp Life (Rated)        | 35,000 hrs | 35,000 hrs | 35,000 hrs | 35,000 hrs |
| Minimum Starting Temp    | -30°C      | -30°C      | -30°C      | -30°C      |

IC-rated for direct contact with insulation



- LED11DR5627K
- LED11DR5630K
- LED11DR5641K
- LED11DR5650K
- LED14DR5627K
- LED14DR5630K
- LED14DR5641K
- LED14DR5650K



- LED10DR427K
- LED10DR430K
- LED10DR435K
- LED10DR441K
- LED10DR450K



- L11DR56D3527K95
- L11DR56D3530K95



- L9DR4D3527K95
- L9DR4D3530K95



**5 YEAR WARRANTY\***

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP AUG 2017/WF72602.ALL





# LED Dimmable Recessed Retrofits Specifications

Smooth Uniform Dimming

## 5/6" Recessed Retrofits

| Item #   | ENERGY STAR rated | Description                             | Life Hours | Replacement | Voltage | Wattage | Lumens | LPW  | CCT   | CRI | Case Qty |
|--|-------------------|---|------------|-------------|---------|---------|--------|------|-------|-----|----------|
| <b>Downlight Retrofits compatible with 5/6" recessed cans</b>        |                   |   |            |             |         |         |        |      |       |     |          |
| LED14DR5627K   | ★                 | LED 14W 5/6" Recessed Downlight - 2700K | 35,000     | 120         | 120     | 14      | 1250   | 89.3 | 2700K | 80  | 6        |
| LED14DR5630K   | ★                 | LED 14W 5/6" Recessed Downlight - 3000K | 35,000     | 120         | 120     | 14      | 1300   | 92.9 | 3000K | 80  | 6        |
| LED14DR5641K   | ★                 | LED 14W 5/6" Recessed Downlight - 4100K | 35,000     | 120         | 120     | 14      | 1300   | 92.9 | 4100K | 80  | 6        |
| LED14DR5650K   | ★                 | LED 14W 5/6" Recessed Downlight - 5000K | 35,000     | 120         | 120     | 14      | 1350   | 96.4 | 5000K | 80  | 6        |
| LED11DR5627K   | ★                 | LED 11W 5/6" Recessed Downlight - 2700K | 35,000     | 85          | 120     | 11      | 800    | 72.7 | 2700K | 80  | 6        |
| LED11DR5630K   | ★                 | LED 11W 5/6" Recessed Downlight - 3000K | 35,000     | 85          | 120     | 11      | 850    | 77.3 | 3000K | 80  | 6        |
| LED11DR5641K   | ★                 | LED 11W 5/6" Recessed Downlight - 4100K | 35,000     | 85          | 120     | 11      | 900    | 81.8 | 4100K | 80  | 6        |
| LED11DR5650K   | ★                 | LED 11W 5/6" Recessed Downlight - 5000K | 35,000     | 85          | 120     | 11      | 950    | 86.4 | 5000K | 80  | 6        |
| <b>Hi CRI Downlight Retrofits compatible with 5/6" recessed cans</b> |                   |   |            |             |         |         |        |      |       |     |          |
| L11DR56D3527K95**  | ★                 | LED 11W 5/6" Recessed Downlight - 2700K | 35,000     | 65          | 120     | 11      | 700    | 63.6 | 2700K | 90  | 6        |
| L11DR56D3530K95**  | ★                 | LED 11W 5/6" Recessed Downlight - 3000K | 35,000     | 65          | 120     | 11      | 750    | 68.2 | 3000K | 90  | 6        |

## 4" Recessed Retrofits

|  |   |                                       |        |    |     |    |     |      |       |    |   |
|--|---|---------------------------------------|--------|----|-----|----|-----|------|-------|----|---|
| <b>Downlight Retrofits compatible with 4" recessed cans</b>        |   |                                       |        |    |     |    |     |      |       |    |   |
| LED10DR427K  | ★ | LED 10W 4" Recessed Downlight - 2700K | 35,000 | 75 | 120 | 10 | 750 | 75.0 | 2700K | 80 | 6 |
| LED10DR430K  | ★ | LED 10W 4" Recessed Downlight - 3000K | 35,000 | 75 | 120 | 10 | 750 | 75.0 | 3000K | 80 | 6 |
| LED10DR435K  |   | LED 10W 4" Recessed Downlight - 3500K | 35,000 | 75 | 120 | 10 | 620 | 62.0 | 3500K | 80 | 6 |
| LED10DR441K  | ★ | LED 10W 4" Recessed Downlight - 4100K | 35,000 | 75 | 120 | 10 | 800 | 80.0 | 4100K | 80 | 6 |
| LED10DR450K  | ★ | LED 10W 4" Recessed Downlight - 5000K | 35,000 | 75 | 120 | 10 | 800 | 80.0 | 5000K | 80 | 6 |
| <b>Hi CRI Downlight Retrofits compatible with 4" recessed cans</b> |   |                                       |        |    |     |    |     |      |       |    |   |
| L9DR4D3527K95**  | ★ | LED 9W 4" Recessed Downlight - 2700K  | 35,000 | 50 | 120 | 9  | 550 | 61.1 | 2700K | 90 | 6 |
| L9DR4D3530K95**  | ★ | LED 9W 4" Recessed Downlight - 3000K  | 35,000 | 50 | 120 | 9  | 550 | 61.1 | 3000K | 90 | 6 |

### Accessory

LDRACCGU24      GU24 Adapter

\*JAB Compliant

+All Plastic Body



**5 YEAR WARRANTY\***

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP AUG 2017/WF72602.ALL



# CREATING BEAUTY

TCP has a **20-year history in energy-efficient lighting.**

Thanks to our **cutting edge technology** and manufacturing

expertise, we have shipped billions of high quality lamps and our

**integrated technology** and manufacturing

provides **expedited time-to-market.** With TCP, you can

count on unique lighting products designed to meet very specific needs—

lighting that transforms your surroundings and envelopes you in warmth—

**lighting that generates beauty** with every flip of the switch.

# LED

For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | F: 877-487-0516