

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

8				
ē	2	i.		
ł.				
i				
1			ŀ	
	A COLORED	-	1077.us	

LPCC5 5A 600V TD Class CC Low Peak Fuse Bussmann Fuses

Catalog Number	LPCC5	
Manufacturer	Bussmann Fuses	
Description	Low Peak Fuse, Time Delay Fuse Speed, Class CC Fuse, 12 S @ 200% Response Time, 5 A, 600 V Ac;150 V DC, Melamine Tube Material, Dual Element, 0.41 In Diameter, 1.5 IN38.1 MM Overa Length, 0.02 LB	
Weight per unit	-	
Product Category	Current Limiting	
eatures		
amperage rating	5	
connection	Ferrule End X Ferrule End	
dimensions	0.4100 IN X 0.4100 IN X 1.5000 IN	
element	Dual	
media	Yes	
Dimensions and Weight		
Size	13/32 In Diameter X 1-1/2 In Length	
escriptions		
Description	5A 600V TD CLASS CC LOW PEAK FUSE	
extra long description	BUSS LP-CC-5 LOW PEAK CC TIME DELAY	
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or	
Special Features	Rejection Style	
Anufacturer Information		
Brand	COOPER BUSSMANN	
GTIN	00051712180337	
UPC	051712180337	
axonomies, Classifications, and	Categories	
Category Description		
Туре	FUSE	



$E_{\text{LLIOTT}} E_{\text{LECTRIC}} S_{\text{UPPLY}}$

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	10
Weight Per each	0.02
Uses, Certifications, and Standards	
standard	UL Listed ,CSA Certified,CE Marked,RoHS Compliant