

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPJ412SP 4-1/2A 600V J TD Fuse Bussmann Fuses

Catalog Number	LPJ412SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class J Fuse, LPJ, Time-Delay,
	Dual-Element Current Limiting Fuse, 4.5 A, Non-Idicating Fuse,
	Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC
Weight per unit	0.1900 (lbs/each)
Product Category	Tools & Testers
eatures	
amperage rating	4.5A
class	Class J
connection	Formula Fred V Formula Fred
dimensions	
element	Dual
Fuse Class	Class J
interrupt rating	300 kAIC at 600 Vac100 kAIC Vdc
Response Time	
Voltage Rating	
Dimensions and Weight	
Size	0.81 In Diameter X 2.25 In Length
Descriptions	
Description	
extra long description Features	
reatures	Bussmann's UL Class J fuse products extend both our Low-Peak family of products with our LPJ_SP and LPJ_SPI dual-element, time-delay fuses as well as our Limitron line offering fast-acting JKS fuses. The LPJ fuses provide industry leading 300,000 amp interrupting rating at 600Vac RMS Sym and 100kA Vdc while delivering a minimum of 10 seconds of 500 percent rated current ride-through performance which is ideal for sizing of high inrush loads. The LPJ products are available with optional permanent replace fu
Long Description	Eaton Bussmann Series Class J fuse, LPJ, time-delay, dual-elemen current limiting fuse, 4.5 A, non-idicating fuse, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc
Product Type	Low-Peak Class J T/D
Special Features	Indicating, High in-rush current motor protection



ELLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00051712522786
Manufacturers Part Number	LPJ412SP
UPC	051712522786
Taxonomies, Classifications, and Cat	egories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.19
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked, RoHS Compliant