

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPNRK30SP 30A 250V TD Dual Elem Class RK1 Low Peak Fuse

Catalog Number	LPNRK30SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series LPN-RK Fuse, 30 A, Dual, Class RK1, Non-Indicating, Ferrule End X Ferrule End, Time Delay, Current-Limiting, 8 Sec At 500%, 300 Kaic At 250 V, 100 Kaic At 125 VDC, Standard, 10
Weight per unit	0.0500 (lbs/each)
Product Category	Dual Element
tures	
amperage rating	30 A
class	Class RK1
connection	Ferrule End X Ferrule End
dimensions	2.0000 IN X 0.5600 IN X 0.5600 IN
element	Dual
interrupt rating	300 kAIC at 250 Vac100 kAIC at 125 Vdc
media	Yes
Response Time	8 S at 500%
Voltage Rating	250 VAC, 125 VDC
nensions and Weight	
Size	0.56 In Diameter X 2.00 In Length

Dim

Desc

30A 250V TD DUAL ELEM CLASS RK1 LOW PEAK FUSE
BUSS LPN-RK-30SP LOW PEAK DUAL ELEM
Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses.
Eaton Bussmann series LPN-RK fuse, 30 A, Dual, Class RK1, Non-indicating, Ferrule end x ferrule end, Time delay, Current-limiting, 8 sec at 500%, 300 kAIC at 250 V, 100 kAIC at 125 Vdc, Standard, 10
Low Peak Dual Element
Indicating, High in-rush current motor protection



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	-	•			
I	$H \cap V$	いいせへん	tiirar	INTARK	MATIAN
ı۱	//	111141			114116111
	viui	IGIGG	tai Ci		nation

Brand	Eaton	
GTIN	00051712538367	
Manufacturers Part Number	LPN-RK-30SP	
UPC	051712538367	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

gg	
Carton	10
Weight Per each	0.05

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked